

RACKCONSOLE-PRO 17HR-BE+F-USB

KVM add-ons, Article number A3200084



The RackConsole-PRO is a key drawer and enables direct access to servers mounted in a rack. The key drawer is a stand-alone device and compatible with many G&D devices.

SCOPE OF DELIVERY

| Quantity | Description | Article number |
|----------|--|----------------|
| 1 | PowerCable-2 Standard cable 2m | A6300057 |
| 1 | DVI-I zu DVI-D AdapterInLine 1776OP für RackConsole | Z0006128 |
| 1 | DVI-I zu DVI-A VGA AdapterInLine 17790P für RackConsole | Z0006129 |
| 1 | Karton RackConsole mit Zubehör e37747w, 823x560x120, 2.40 EB | VP100014 |
| 1 | Safety instructions flyer - FCC class B | A9100371 |

DETAILS

VIDEO

- Max. resolution:
 - 1920 × 1200 at 60 Hz (digital and analog)
 - 2560 × 1600 at 60 Hz (digital, scaled)
- Color mode: digital 24 bit
- Variable video inputs:
 - DVI-I (digital/analog)
 - DisplayPort
 - HDMI

DEVICE

- Display: TFT LCD with LED backlight
- USB port for keyboard and mouse
- Transparent USB 3.0 interface on front panel
- Optimized industrial video panel
- High-quality and durable control elements
- Robust case and components especially designed for use in server rooms or industrial environments
- Optimal protection of controls and panel when folded up
- Smooth-running mechanism with nevertheless firm locking for opening and closing the display lid
- Reinforced and precisely tuned telescopic rails for stable installation in racks of any depth
- Special robust energy chain to protect cables
- Internal power pack for main power supply

WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

FEATURES

OPERATION FEATURES

- Mouse control via built-in touchpad
- On-screen display for operation and configuration
- Automatic power on/off when opening/closing the display

EXTENSIONS

DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply

TECHNICAL DATA

| | | |
|----------------------|--|-----------------------------------|
| General | Product group | KVM add-ons |
| | Product Family | RackConsole-Pro |
| | Power Supply | Redundancy without load balancing |
| Input options | USB mouse | yes |
| | USB keyboard | yes |
| Maintenance | Update via | no update possibility |
| Housing | Material | Steel sheet |
| | Width ca. | 483 mm |
| | Height ca. | 44 mm |
| | Depth ca. | 628 mm |
| | IP protection class | IP20 |
| | Weight ca. | 13.46 kg |
| Operating conditions | Operating environment temperature | 5 °C to 45 °C |
| | Operating air humidity, non-condensing | 20 % to 60 % |
| | Area of application | Indoor use |
| | Maximum operating altitude above sea level | 3,000 m |
| | Storage environment temperature | -20 °C to 60 °C |
| | Storage air humidity, non-condensing | 15 % to 70 % |

| | | |
|----------------|------------------------|---|
| | MTBF | 50,000 h at 25°C |
| | Conformities | CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads) |
| Power supply 1 | Quantity | 1 |
| | Type | Internal |
| | Input voltage | 100-240 VAC |
| | Input frequency | 60-50 Hz |
| | Current consumption | 1.1-0.6 A |
| | Power consumption idle | 0.58-0.43 W |
| | Power consumption max. | 49.2-48.4 W |
| | Heat output idle | 0.58-0.43 W |
| | Heat output max. | 44.7-44.3 W |
| Power supply 2 | Quantity | 1 |
| | Type | External |
| | Input voltage | 12 VDC |
| | Current consumption | 4.2 A |
| | Power consumption idle | 0.48 W |
| | Power consumption max. | 48 W |

| | | |
|--|------------------|--------|
| | Heat output idle | 0.48 W |
| | Heat output max. | 43.5 W |

ACCESSORY PRODUCTS

| Image | Description | Article number |
|---|---|----------------|
|  | PowerCable-3 Standard cable 3m Cable to connect the power supply type Germany | A6300066 |
|  | PowerCable-5 Standard cable 5m Cable to connect the power supply type Germany | A6300065 |

MORE VARIANTS

| Description | Article number |
|---|----------------|
| RackConsole-PRO 17HR-CH+D-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Swiss German, with touchpad | A3200085 |
| RackConsole-PRO 17HR-DE-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout German, with touchpad | A3200086 |
| RackConsole-PRO 17HR-ES-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Spanish, with touchpad | A3200087 |
| RackConsole-PRO 17HR-FR-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout French, with touchpad | A3200088 |
| RackConsole-PRO 17HR-Nord-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Nordic, with touchpad | A3200089 |
| RackConsole-PRO 17HR-RU-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Russian, with touchpad | A3200090 |
| RackConsole-PRO 17HR-UK-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout UK English, with touchpad | A3200091 |
| RackConsole-PRO 17HR-US-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout US English, with touchpad | A3200092 |

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +49 271 23872-333
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung
Obere Leimbach 9 | 57074 Siegen | NRW |
Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Guntermann & Drunck GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales.me@gdsys.com

APAC OFFICE

Guntermann & Drunck GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales.apac@gdsys.com