

RACKCONSOLE-PRO 17HR-US-USB

KVM add-ons, Article number A3200092



The RackConsole-PRO is a key drawer and enables direct access to servers mounted in a rack. The key drawer is a stand-alone device and compatible with many G&D devices.

SCOPE OF DELIVERY

Quantity	Description	Article number
1	PowerCable-2 Standard cable 2m	A6300057

DETAILS

VIDEO

- Max. resolution:
 - 1920 × 1200 at 60 Hz (digital and analog)
 - 2560 × 1600 at 60 Hz (digital, scaled)
- Color mode: digital 24 bit
- Variable video inputs:
 - DVI-I (digital/analog)
 - DisplayPort
 - HDMI

DEVICE

- Display: TFT LCD with LED backlight
- USB port for keyboard and mouse
- Transparent USB 3.0 interface on front panel
- Optimized industrial video panel
- High-quality and durable control elements
- Robust case and components especially designed for use in server rooms or industrial environments
- Optimal protection of controls and panel when folded up
- Smooth-running mechanism with nevertheless firm locking for opening and closing the display lid
- Reinforced and precisely tuned telescopic rails for stable installation in racks of any depth
- Special robust energy chain to protect cables
- Internal power pack for main power supply

WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension/guarantee renewal possible



FEATURES

OPERATION FEATURES

- Mouse control via built-in touchpad
- On-screen display for operation and configuration
- Automatic power on/off when opening/closing the display

EXTENSIONS

DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply

TECHNICAL DATA

General	Product group	KVM-Add-ons
Input options	USB mouse	yes
	USB keyboard	yes
Maintenance	Update via	no update possibility
Housing	Material	Steel sheet
	Width	ca. 483 mm
	Height	ca. 44 mm
	Depth	ca. 628 mm
	IP protection class	IP20
	Weight	ca. 13.46 kg
Operating conditions	Operating temperature	5 °C to 45 °C
	Operating air humidity	20 % to 60 %, non-condensing
	Area of application	Interior
	Maximum operating altitude	3000m above sea level
	Storage temperature	-20 °C to 60 °C
	Storage air humidity	15 % to 70 %, non-condensing
	MTBF	50000 h at 25°C

	Conformities	CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)
	Input voltage	100-240 VAC
	Input frequency	60-50 Hz
	Current consumption	1.1-0.6 A
	Power consumption idle	0.58-0.43 W
	Power consumption max.	49.2-48.4 W
	Heat output idle	0.58-0.43 W
Power supply	Heat output max.	44.7-44.3 W
	Input voltage	12 VDC
	Current consumption	4.2 A
	Power consumption idle	0.48 W
	Power consumption max.	48 W
	Heat output idle	0.48 W
	Heat output max.	43.5 W
Power supply 2		

MORE VARIANTS

Description	Article number
RackConsole-PRO 17HR-BE+F-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Belgium French, with touchpad	A3200084
RackConsole-PRO 17HR-CH+D-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Swiss German, with touchpad	A3200085
RackConsole-PRO 17HR-DE-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout German, with touchpad	A3200086
RackConsole-PRO 17HR-ES-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Spanish, with touchpad	A3200087
RackConsole-PRO 17HR-FR-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout French, with touchpad	A3200088
RackConsole-PRO 17HR-Nord-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Nordic, with touchpad	A3200089
RackConsole-PRO 17HR-RU-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Russian, with touchpad	A3200090
RackConsole-PRO 17HR-UK-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout UK English, with touchpad	A3200091

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +1-833-928-1976
Fax: +1-833-928-1976
E-Mail: sales.us@gdsys.com

HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung
Obere Leimbach 9 | 57074 Siegen | NRW |
Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Guntermann & Drunck GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales.me@gdsys.com

APAC OFFICE

Guntermann & Drunck GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales.apac@gdsys.com