# AUDIO-TRANSCEIVER-CAT INCL. POWERPACK

KVM extenders, Article number A1990030



Front



Back

The Audio-Transceiver is a stand-alone device for transmitting analog and digital (SPDIF) stereo audio signals over distances of up to 10,000 m. Such a single signal extender system consists of a computer module (transmitter) and console module (receiver). The product can be used flexibly as a transmitter or receiver. Two devices are required for a complete system. Transmission takes place via a CAT or fiber connection.

## SCOPE OF DELIVERY

| Quantity | Description | Article number |
|---|---|---|
| 1 | Netzteil 12V / 2,08AFSP025-D12C14 FSP | Z0005926 |
| 1 | PowerCable-2 Standard cable 2m | A6300057 |
| 1 | Audio-M/M-2-ferrite cable 2m | A6300083 |
| 1 | Audio-SPDIF-COAX-M/M-2 cable SPDIF 2m | A6300119 |
| 1 | Safety instructions flyer - FCC class B | A9100371 |

# DETAILS

## SIGNALS

- Amplifiable input signal for microphones etc.
- Bidirectional audio signals in stereo/CD quality
- Digital audio signale (2 channel LPCM, consumer, PCM stereo)

## TRANSMISSION

- The transmission distance is up to 140 meters over CAT

## DEVICE

- External power supply

## WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

# TECHNICAL DATA

| | | |
|---|---|---|
| General | Brand | G&D |
| | Product group | KVM extenders |
| | Product Family | Audio-Transceiver |
| | Country of origin | Germany |
| | Number of sources | 1 |
| | Power Supply | no redundancy |
| Transmission | Number of transmission channels | 1 |
| | Redundant transmission channels | no redundant KVM transmission |
| | Range | 140 m (AWG22)<br>100 m (AWG24)<br>80 m (AWG26) |
| | Medium | CAT5e<br>CAT6<br>CAT7 |
| | Data rate | 1 Gbit/s |
| Audio 1 | Transmission type | Bidirectional<br>Stereo |
| | Resolutions | 24 bit digital |
| | Sampling rate | up to 192 kHz |
| | Bandwidth | 22 kHz |
| | Audio support | Analog |

| | | |
|---|---|---|
| Audio 2 | Transmission type | Consumer<br>SPDIF<br>Stereo<br>2-channel LPCM |
| | Resolutions | 24 bit |
| | Sampling rate | up to 48 kHz<br>up to 96 kHz<br>up to 192 kHz |
| | Bandwidth | 22 kHz |
| | Audio support | Digital |
| Maintenance | Update via | Update Wizard (service interface) |
| | Serviceport settings | 115200bps (8/N/1) |
| Housing | Material | Anodised aluminium |
| | Active cooling (fan) | no |
| | Width ca. | 105 mm / 4.13 in |
| | Height ca. | 26 mm / 1.02 in |
| | Depth ca. | 84 mm / 3.31 in |
| | IP protection class | IP20 |
| | Weight ca. | 0.2 kg / 0.44 lb |
| Operating conditions | Operating environment temperature | 5 °C to 45 °C / 41 °F to 113 °F |
| | Operating air humidity, non-condensing | 20 % to 80 % |
| | Area of application | Indoor use |

| | | |
|---|---|---|
| | Maximum operating altitude above sea level | 3,048 m |
| | Storage environment temperature | -10 °C to 55 °C / 14 °F to 131 °F |
| | Storage air humidity, non-condensing | 15 % to 80 % |
| | MTBF | 300,000 h at 25°C (77 °F) |
| | Conformities | CE compliant (see downloads)<br>UKCA compliant (see downloads)<br>FCC compliant (see manual)<br>TAA compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads) |
| Power supply | Quantity | 1 |
| | Type | External |
| | Input voltage | 12 VDC |
| | Current consumption | 0.3 A |
| | Power consumption idle | 1.68 W |
| | Power consumption max. | 2.22 W |
| | Heat output idle | 1.68 W / 5.73 BTU/h |
| | Heat output max. | 2.22 W / 7.57 BTU/h |

# ACCESSORY PRODUCTS

| Image | Description | Article number |
|---|---|---|
| | **USB-Service-2 cable 2m**<br>Cable for system updates and configuration | A6200103 |
| | **Audio-M/M-3-ferrite cable 3m**<br>Audio connection cable with ferrite core | A6300118 |
| | **Audio-M/M-5-ferrite cable 5m**<br>Audio connection cable with ferrite core | A6300085 |
| | **PowerCable-3 Standard cable 3m**<br>Cable to connect the power supply type Germany | A6300066 |
| | **PowerCable-5 Standard cable 5m**<br>Cable to connect the power supply type Germany | A6300065 |
|  | **CaseMount-Set-105-26 mounting bracket**<br>Screws & brackets for mounting devices with dimensions 105x26mm in DeviceCarriers | A7000020 |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.


### TECHNICAL SALES

Tel.: +49 271 23872-333
Fax: +49 271 23872-120
E-Mail: sales@panoptec.com

### HEADQUARTERS

Panoptec Europe GmbH
Obere Leimbach 9 | 57074 Siegen | NRW | Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@panoptec.com

### US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

### MIDDLE EAST OFFICE

Panoptec Europe GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales@panoptec.com

### APAC OFFICE

Panoptec Europe GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales@panoptec.com