

DL-VISION(S)-MC2-AR-CON

KVM extenders, Article number A1220052



The KVM extenders of the DL-Vision series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated fiber connection (up to 10,000 m) uncompressed, pixel-perfect and without any latency or loss. An extender system consists of a computer module (CPU) and a console module (CON). The DL-Vision series supports DualLink-DVI for high-resolution video up to 2560 × 1600 (60 Hz) or 4096 × 2160 (30 Hz).

SCOPE OF DELIVERY

Quantity	Description	Article number
2	PowerCable-2 Standard cable 2m	A6300057
1	19" RM-Set-436-1RU-Type2	A7000011

DETAILS

VIDEO

- EDID data utilization from the workplace monitor
- Flexible EDID profile options for optimized monitor settings
- Resolution up to
2560 × 1600 @ 60 Hz

SIGNALS

- Transparent audio signals (stereo, analog)
- Transparent RS232 (max. 230,400 bps)

TRANSMISSION

- The transmission distance is up to 10,000 meters over fiber singlemode optics, incl. transmission module(s)/ SFP transceiver(s)

DEVICE

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- MultiChannel variants (MC): Modules for multi-monitor workplaces with multi-channel video
 - MC mode uses the full bandwidth for each video channel, whereby a separate transmission line is required for each channel

WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension/guarantee renewal possible

FEATURES

SECURITY FEATURES

- Early detection of security incidents or unusual activities through continuous monitoring via Syslog, monitoring, and SNMP
- Comprehensive rights management and user administration, allowing precise control over which user can access which resources
- Option for activatable access protection (default operating mode in matrix systems), in which authentication is required before accessing computer sources
- Support for external directory services (Active Directory, Radius, LDAP) to meet company security policies
- Freeze function: If the video signal is lost, the last displayed image is frozen and highlighted with a colored frame and timer
- Redundant internal power packs
- Redundant network interface

OPERATION FEATURES

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Operation via multilingual on-screen display (OSD) and hotkeys
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness
- Local console at the computer module allows on-site operation, including all video channels
- Exclusive or concurrent operation: The KVM extender allows computer control both remotely and locally. When an input is detected, the extender automatically locks the competing console. The lock is lifted after a preset timeout if no further input is detected. A key combination can activate exclusive operation, immediately disabling the competing console. Another key combination restores shared control.

TECHNICAL DATA

General	Product group	KVM extenders
Input options	USB mouse	yes
	USB keyboard	yes
	PS/2 mouse	yes
	PS/2 keyboard	yes
Transmission	Number of transmission channels	2
	Redundant transmission channels	no redundant KVM transmission
	Range	10000 m (9/125µm, OS1)
	Laser class	Class 1
	Type of interface	LC-Duplex
	Wavelength	1310 nm
	Medium	Fiber SM
	Data rate	10 Gbit/s
Video output	Number of video channels	2
	Format	DualLink DVI
	Colour depth	24 bit
	Pixel rate	ca. 25 MPixel/s to ca. 330 MPixel/s
	Vertical frequency	20 Hz to 120 Hz
	Horizontal frequency	25 kHz to 185 kHz

	Exemplary resolutions	2560 × 1600 (60 Hz) - 2K / WQXGA 4096 × 2160 (30 Hz) - 2K / WQXGA 2048 × 2160 (60 Hz) - 2K / WQXGA 2048 × 2048 (60 Hz) - 2K / WQXGA 3840 × 2160 (30 Hz) - 2K / WQXGA Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.
	Supported industry standards	Enhanced Display Data Channel (E-DDC) Display Data Channel Command Interface (DDC/CI)
Audio	Transmission type	Stereo Transparent
	Resolutions	24 bit digital
	Sampling rate	up to 96 kHz
	Bandwidth	22 kHz
	Audio support	Analog
Serial	Standard	RS232
	Transparent transmission	yes
	Data rate	max. 230400 bps
	Signals	TxD RxD DTR DSR RTS CTS DCD
Network	Medium 1	CAT7 CAT6 CAT5

	Data rate 1	10 MBit/s 100 MBit/s 1 GBit/s
	Medium 2	CAT5 CAT6 CAT7
	Data rate 2	10 MBit/s 100 MBit/s 1 GBit/s
Maintenance	Update via	ConfigPanel (Network)
	Serviceport settings	230400bps (8/N/1)
Housing	Material	anodised aluminium
	Width	ca. 436 mm
	Height	ca. 44 mm
	Depth	ca. 284 mm
	IP protection class	IP20
	Weight	ca. 3.06 kg
Operating conditions	Operating temperature	5 °C to 45 °C
	Operating air humidity	up to 80 %, non-condensing
	Area of application	Interior
	Maximum operating altitude	3048m above sea level
	Storage temperature	-10 °C to 55 °C
	Storage air humidity	up to 85 %, non-condensing
	MTBF	150000 h at 25°C

	Conformities	CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)
Power supply	Input voltage	100-240 VAC
	Input frequency	60-50 Hz
	Current consumption	0.7-0.3 A
	Power consumption max.	26.7-26.8 W
	Heat output max.	23.7-23.8 W
Power supply 2	Input voltage	100-240 VAC
	Input frequency	60-50 Hz
	Current consumption	0.7-0.3 A
	Power consumption max.	26.7-26.8 W
	Heat output max.	23.7-23.8 W



MORE VARIANTS

Description	Article number
DL-Vision(S)-AR-CON Console module to receive Dual-Link-DVI signals via fiber singlemode	A1220048
DL-Vision(S)-ARU2+CON Console module to receive Dual-Link-DVI signals via fiber singlemode	A1220215
DL-Vision(S)-MC2-ARU2+CON Console module to receive Dual-Link-DVI signals via fiber singlemode	A1220216

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +1-833-928-1976
Fax: +1-833-928-1976
E-Mail: sales.us@gdsys.com

HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung
Obere Leimbach 9 | 57074 Siegen | NRW |
Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Guntermann & Drunck GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales.me@gdsys.com

APAC OFFICE

Guntermann & Drunck GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales.apac@gdsys.com