



# DP-CPU 2.0 BASIC

KVM extenders, Article number A2320081



Front



Back

The matrix-compatible KVM extenders of the DP-CPU series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated CAT connection (up to 140 m). An extender system consists of a computer module (CPU) and a compatible console module (CON). Computers can be controlled in near real-time – both in extender and matrix applications. The DP-CPU series supports DisplayPort1.1 DualMode (DP++) for video resolutions up to 1920 x 1200 (60 Hz). Video data is processed pixel-perfectly and offers excellent hand-eye coordination, thanks to bluedec™ – G&D's advanced, multi-stage, lossless compression technology.

## SCOPE OF DELIVERY

| Quantity | Description                  | Article number |
|----------|------------------------------|----------------|
| 1        | USB-AM/BM-2 cable USB 2m     | A6300113       |
| 2        | Audio-M/M-2-ferrite cable 2m | A6300083       |
| 1        | DP1.4-Cable-M/M-2 SK13357 2m | A6300173       |

## DETAILS

### VIDEO

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- Use of a monitor profile optimized for the computer module (EDID profile)
- Flexible use of the EDID data of the workplace monitor as required
- Use of the VESA DisplayPort DualMode standard version 1.1 (extension to the DisplayPort 1.1a standard)
- For correct operation, the DisplayPort source also needs to support the DualMode standard (often marked with DP++)
- Resolution up to 1920 x 1200 @ 60 Hz

### SIGNALS

- Bidirectional audio signals (stereo)

### TRANSMISSION

- The transmission distance is up to 140 meters over CAT

### DEVICE

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)
- PowerPack not included in the scope of delivery for Basic variants
- UC variant: computer module with two transmission lines for redundancy
  - These modules can be connected to various counterparts, such as compatible console modules or KVM matrix switches
- MultiChannel variants (MC): Modules for multi-monitor workplaces with multi-channel video
  - MC mode uses the full bandwidth for each video channel, whereby a separate transmission line is required for each channel

### WARRANTY

- A 3-year, free of charge product guarantee

- For an additional fee guarantee extension/guarantee renewal possible

## FEATURES

### OPERATION FEATURES

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Compatibility with special USB-HID input devices
- Operation via multilingual on-screen display (OSD) and hotkeys
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness

## EXTENSIONS

### DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply
- Device mounting via RackMount sets, TableMount sets or other mounting tools

### SYSTEM EXTENSION

- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.

## TECHNICAL DATA

|               |                                 |                                                |
|---------------|---------------------------------|------------------------------------------------|
| General       | Product group                   | KVM extenders<br>KVM matrix systems            |
|               | Number of sources               | 1                                              |
| Input options | USB mouse                       | yes                                            |
|               | USB keyboard                    | yes                                            |
|               | PS/2 mouse                      | yes                                            |
|               | PS/2 keyboard                   | yes                                            |
| Transmission  | Number of transmission channels | 1                                              |
|               | Redundant transmission channels | no redundant KVM transmission                  |
|               | Range                           | 140 m (AWG22)<br>100 m (AWG24)<br>80 m (AWG26) |
|               | KVM matrix system component     | Computer module                                |
|               | Medium                          | CAT5e<br>CAT6<br>CAT7                          |
|               | Data rate                       | 1 Gbit/s                                       |
|               |                                 |                                                |
| Video input   | Number of video channels        | 1                                              |
|               | Format                          | DisplayPort 1.1<br>(DualMode)                  |
|               | Colour depth                    | 24 bit                                         |
|               | Pixel rate                      | ca. 25 MPixel/s to ca. 165 MPixel/s            |
|               | Vertical frequency              | 50 Hz to 180 Hz                                |

|             |                              |                                                                                                                                                                                  |
|-------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|             | Horizontal frequency         | 30 kHz to 130 kHz                                                                                                                                                                |
|             | Exemplary resolutions        | 1920 × 1200 (60 Hz)<br>1920 × 1080 (60 Hz)<br>1600 × 1200 (60 Hz)<br>Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency. |
|             | Supported industry standards | Display Data Channel (DDC)<br>Display Data Channel Command Interface (DDC/CI)                                                                                                    |
| Audio       | Transmission type            | Bidirectional<br>Stereo                                                                                                                                                          |
|             | Resolutions                  | 24 bit digital                                                                                                                                                                   |
|             | Sampling rate                | up to 96 kHz                                                                                                                                                                     |
|             | Bandwidth                    | 22 kHz                                                                                                                                                                           |
|             | Audio support                | Analog                                                                                                                                                                           |
| Maintenance | Update via                   | Update Wizard (service interface)                                                                                                                                                |
|             | Serviceport settings         | 115200bps (8/N/1)                                                                                                                                                                |
| Housing     | Material                     | anodised aluminium                                                                                                                                                               |
|             | Width                        | ca. 105 mm                                                                                                                                                                       |
|             | Height                       | ca. 26 mm                                                                                                                                                                        |
|             | Depth                        | ca. 104 mm                                                                                                                                                                       |
|             | IP protection class          | IP20                                                                                                                                                                             |
|             | Weight                       | ca. 0.26 kg                                                                                                                                                                      |

|                      |                            |                                                                                                                                                                                                                                                                   |
|----------------------|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating conditions | Operating temperature      | 5 °C to 45 °C                                                                                                                                                                                                                                                     |
|                      | Operating air humidity     | 20 % to 80 %, non-condensing                                                                                                                                                                                                                                      |
|                      | Area of application        | Interior                                                                                                                                                                                                                                                          |
|                      | Maximum operating altitude | 3048m above sea level                                                                                                                                                                                                                                             |
|                      | Storage temperature        | -20 °C to 60 °C                                                                                                                                                                                                                                                   |
|                      | Storage air humidity       | 15 % to 85 %, non-condensing                                                                                                                                                                                                                                      |
|                      | MTBF                       | 280000 h at 25°C                                                                                                                                                                                                                                                  |
|                      | Conformities               | CE compliant (see downloads)<br>UKCA compliant (see downloads)<br>FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads) |
| Power supply         | Input voltage              | 12 VDC                                                                                                                                                                                                                                                            |
|                      | Current consumption        | 0.5 A                                                                                                                                                                                                                                                             |

## MORE VARIANTS

| Description                                                                                                                                                                        | Article number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>DP-CPU 2.0 Incl. PowerPack</b><br>Computer module to extend DisplayPort signals via CAT cable                                                                                   | A2320078       |
| <b>DP-CPU 4.0 Basic</b><br>Computer module to extend DisplayPort signals via CAT cable                                                                                             | A2320495       |
| <b>DP-CPU 4.0 Incl. Powerpack</b><br>Computer module to extend DisplayPort signals via CAT cable                                                                                   | A2320496       |
| <b>DP-CPU-UC 2.0 Basic</b><br>Computer module for transmission of DisplayPort signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable             | A2320080       |
| <b>DP-CPU-UC 2.0 Incl. PowerPack</b><br>Computer module for transmission of DisplayPort signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable   | A2320079       |
| <b>DP-CPU-UC 4.0 Basic</b><br>Computer module for transmission of DisplayPort signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable             | A2320497       |
| <b>DP-CPU-UC 4.0 Incl. Powerpack</b><br>Computer module for transmission of DisplayPort signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable   | A2320498       |
| <b>DP-U-CPU 4.0 Basic</b><br>Computer module to extend DisplayPort signals via CAT cable                                                                                           | A2320499       |
| <b>DP-U-CPU 4.0 Incl. Powerpack</b><br>Computer module to extend DisplayPort signals via CAT cable                                                                                 | A2320500       |
| <b>DP-U-CPU Basic</b><br>Computer module to extend DisplayPort signals via CAT cable                                                                                               | A2320122       |
| <b>DP-U-CPU Incl. PowerPack</b><br>Computer module to extend DisplayPort signals via CAT cable                                                                                     | A2320121       |
| <b>DP-U-CPU-UC 4.0 Basic</b><br>Computer module for transmission of DisplayPort signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable           | A2320501       |
| <b>DP-U-CPU-UC 4.0 Incl. Powerpack</b><br>Computer module for transmission of DisplayPort signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable | A2320502       |

| Description                                                                                                                                                                             | Article number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>DP-U-CPU-UC Basic</b><br>Splitter computer module for transmission of DisplayPort signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable           | A2320124       |
| <b>DP-U-CPU-UC incl. PowerPack</b><br>Splitter computer module for transmission of DisplayPort signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable | A2320123       |



# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +49 271 23872-333  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)