

**Guntermann & Drunck GmbH Systementwicklung**  
Obere Leimbach 9 | 57074 Siegen | Germany | T +49 271 23872-0 | F +49 271 23872-120 |  
[sales@gdsys.com](mailto:sales@gdsys.com) | [www.gdsys.com](http://www.gdsys.com)

G&D Product data sheet - 29. Oct 2025 [DVI-CON-Fiber\(S\) 3.0](#)

# DVI-CON-Fiber(S) 3.0

**KVM extenders, Article number A1120264**

Front

Back

The matrix-compatible KVM extenders of the DVI-CON series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated CAT or fiber connection (up to 10,000 m). An extender system consists of a computer module (CPU) and a compatible console module (CON). Computers can be controlled in near real-time – both in extender and matrix applications. The DVI-CON series supports SingleLink DVI for digital video resolutions up to  $1920 \times 1200$  (60 Hz). Video data is processed pixel-perfectly and offers excellent hand-eye coordination, thanks to bluedec™ – G&D's advanced, multi-stage, lossless compression technology.

## Scope of delivery

| Quantity | Description                    | Article number |
|----------|--------------------------------|----------------|
| 1        | PowerCable-2 Standard cable 2m | A6300057       |

## Details

### Video

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- Use of a monitor profile optimized for the computer module (EDID profile)
- Flexible use of the EDID data of the workplace monitor as required
- Resolution up to  
 $1920 \times 1200$  @ 60 Hz,  
 $1280 \times 1024$  @ 85 Hz

### Signals

- Bidirectional audio signals (stereo)

### Transmission

- The transmission distance is up to 5,000 meters over fiber singlemode optics, incl. transmission module(s)/SFP transceiver(s)

### Device

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)

- Internal power pack for main power supply
- CON-2 variant: console module with two transmission lines for redundancy
  - These modules can be connected to various counterparts, such as compatible computer modules or KVM matrix switches, whereby switching is carried out via pushbuttons, hotkeys or automatically, depending on the configuration
- MultiChannel variants (MC): Modules for multi-monitor workplaces with multi-channel video
  - MC mode uses the full bandwidth for each video channel, whereby a separate transmission line is required for each channel

## **Warranty**

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

## **Features**

### **Security features**

- Console modules do not store security-relevant information such as login credentials, which could be extracted in the event of device loss

### **Operation features**

- Ready for operation out of the box, no additional configuration required
- Operation via multilingual on-screen display (OSD) and hotkeys
- Compatibility with special USB-HID input devices
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness

## **Extensions**

### **Device**

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply
- Device mounting via RackMount sets, TableMount sets or other mounting tools

### **System extension**

- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.

## Technical data

|                      |                                 |                                                                                                             |
|----------------------|---------------------------------|-------------------------------------------------------------------------------------------------------------|
| <b>General</b>       | Product group                   | KVM extenders                                                                                               |
|                      | Product Family                  | MTX-CPU/CON                                                                                                 |
|                      | Number of workstations          | 1                                                                                                           |
|                      | KVM matrix system component     | Console module (digital)                                                                                    |
|                      | Power Supply                    | Redundancy without load balancing                                                                           |
| <b>Input options</b> | USB mouse                       | yes                                                                                                         |
|                      | USB keyboard                    | yes                                                                                                         |
|                      | PS/2 mouse                      | yes                                                                                                         |
|                      | PS/2 keyboard                   | yes                                                                                                         |
|                      | Number of transmission channels | 1                                                                                                           |
| <b>Transmission</b>  | Redundant transmission channels | no redundant KVM transmission                                                                               |
|                      | Range                           | 5,000 m (9/125µm, OS1)                                                                                      |
|                      | Laser class                     | Class 1                                                                                                     |
|                      | Type of interface               | LC-Duplex                                                                                                   |
|                      | Wavelength                      | 1,310 nm                                                                                                    |
|                      | Medium                          | Fiber SM                                                                                                    |
|                      | Data rate                       | 2.5 Gbit/s                                                                                                  |
|                      | Quantity                        | 1                                                                                                           |
|                      | Format                          | Singlelink DVI                                                                                              |
|                      | Colour depth                    | 24 bit                                                                                                      |
| <b>Video output</b>  | Pixel rate ca.                  | 25 MHz to 165 MHz                                                                                           |
|                      | Vertical frequency              | 50 Hz to 180 Hz                                                                                             |
|                      | Horizontal frequency            | 30 kHz to 130 kHz                                                                                           |
|                      | Exemplary resolutions           | 1920 × 1200 (60 Hz)                                                                                         |
|                      |                                 | 1920 × 1080 (60 Hz)                                                                                         |
|                      |                                 | 1600 × 1200 (60 Hz)                                                                                         |
|                      |                                 | 1280 × 1024 (85 Hz)                                                                                         |
|                      |                                 | 1280 × 1024 (60 Hz)                                                                                         |
|                      | General Notes                   | Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency. |
|                      | Supported industry standards    | Display Data Channel Command Interface (DDC/CI)<br>Display Data Channel (DDC)                               |
|                      | Transmission type               | Bidirectional<br>Stereo                                                                                     |
| <b>Audio</b>         | Resolutions                     | 24 bit digital                                                                                              |
|                      | Sampling rate                   | up to 96 kHz                                                                                                |
|                      | Bandwidth                       | 22 kHz                                                                                                      |
|                      | Audio support                   | Analog                                                                                                      |
| <b>Maintenance</b>   | Update via                      | Update Wizard (service interface)                                                                           |

|                             |                                            |                                 |
|-----------------------------|--------------------------------------------|---------------------------------|
| <b>Housing</b>              | Serviceport settings                       | 115200bps (8/N/1)               |
|                             | Material                                   | anodised aluminium              |
|                             | Width ca.                                  | 210 mm                          |
|                             | Height ca.                                 | 44 mm                           |
|                             | Depth ca.                                  | 210 mm                          |
|                             | IP protection class                        | IP20                            |
|                             | Weight ca.                                 | 1.25 kg                         |
|                             | Operating temperature                      | 5 °C to 45 °C                   |
|                             | Operating air humidity, non-condensing     | 20 % to 80 %                    |
|                             | Area of application                        | Indoor use                      |
| <b>Operating conditions</b> | Maximum operating altitude above sea level | 3,000 m                         |
|                             | Storage temperature                        | -20 °C to 60 °C                 |
|                             | Storage air humidity, non-condensing       | 15 % to 85 %                    |
|                             | MTBF                                       | 200,000 h at 25°C               |
|                             | Conformities                               | CE compliant (see downloads)    |
|                             |                                            | UKCA compliant (see downloads)  |
|                             |                                            | FCC compliant (see manual)      |
|                             |                                            | TAA compliant (see downloads)   |
|                             |                                            | EAC compliant (see downloads)   |
|                             |                                            | RoHS compliant (see downloads)  |
|                             |                                            | WEEE (reg. no. DE30763240)      |
|                             |                                            | REACH compliant (see downloads) |
| <b>Power supply 1</b>       | Quantity                                   | 1                               |
|                             | Type                                       | Internal                        |
|                             | Input voltage                              | 100-240 VAC                     |
|                             | Input frequency                            | 60-50 Hz                        |
|                             | Current consumption                        | 0.3-0.2 A                       |
| <b>Power supply 2</b>       | Quantity                                   | 1                               |
|                             | Type                                       | External                        |
|                             | Input voltage                              | 12 VDC                          |
|                             | Current consumption                        | 1.1 A                           |

accessory products

| Image | Description                                                                             | Article number |
|-------|-----------------------------------------------------------------------------------------|----------------|
|       | <b>USB-Service-2 cable 2m</b><br>Cable for system updates and configuration             | A6200103       |
|       | <b>PowerCable-3 Standard cable 3m</b><br>Cable to connect the power supply type Germany | A6300066       |

| Image | Description                                                                                                    | Article number |
|-------|----------------------------------------------------------------------------------------------------------------|----------------|
|       | <b>PowerCable-5 Standard cable 5m</b><br>Cable to connect the power supply type Germany                        | A6300065       |
|       | <b>PowerPack 12 Type 3 12V/2A</b><br>24W power supply with 2m powercable                                       | A4110013       |
|       | <b>19" RM-Set-210-1RU</b><br>19" extension for rack mounting devices of 210 mm width within 1RU (44 mm height) | A7000022       |

| Image | Description                                                                                                                                                                   | Article number |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
|       | <b>19" RM-Set-210-1RU incl. DeviceCarrier 1x105-26</b><br>19" extension for combined rack mounting devices of 210 mm width and devices of 105x26 mm within 1RU (44 mm height) | A7000035       |

## related products

| Description                                                                                                                                 | Article number |
|---------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>TS-LED-blue-2</b><br>LED to tag the active console of a TradeSwitch configuration of a matrix, resp. the active channel of a TradeSwitch | A6100168       |
| <b>TS-LED-blue-3</b><br>LED to tag the active console of a TradeSwitch configuration of a matrix, resp. the active channel of a TradeSwitch | A6100169       |
| <b>TS-LED-blue-5</b><br>LED to tag the active console of a TradeSwitch configuration of a matrix, resp. the active channel of a TradeSwitch | A6100170       |

## more variants

| Description                                                                                                          | Article number |
|----------------------------------------------------------------------------------------------------------------------|----------------|
| <b>DVI-CON-2-Fiber(S) 3.0</b><br>Redundant console module to receive DVI signals of 2 sources via fiber singlemode   | A1120266       |
| <b>DVI-CON-Fiber(S)-MC2 3.0</b><br>Console module to receive DVI signals via fiber singlemode                        | A1220224       |
| <b>DVI-U-CON-2-Fiber(S) 3.0</b><br>Redundant console module to receive DVI signals of 2 sources via fiber singlemode | A1120269       |
| <b>DVI-U-CON-Fiber(S) 3.0</b><br>Console module to receive DVI signals via fiber singlemode                          | A1120259       |
| <b>DVI-U-CON-Fiber(S)-MC2 3.0</b><br>Console module to receive DVI signals via fiber singlemode                      | A1220220       |



# Contact

## We are here for you!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### Technical sales

Tel.: +49 271 23872-333  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### Headquarters

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW | Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### Middle East office

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)