



DVI-CPU-MC2 2.0 BASIC

KVM extenders, Article number A2320097



Front



Back

The matrix-compatible KVM extenders of the DVI-CPU series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated CAT or fiber connection (up to 10,000 m). An extender system consists of a computer module (CPU) and a compatible console module (CON). Computers can be controlled in near real-time – both in extender and matrix applications. The DVI-CPU series supports SingleLink DVI for digital video resolutions up to 1920 × 1200 (60 Hz). Video data is processed pixel-perfectly and offers excellent hand-eye coordination, thanks to bluedec™ – G&D's advanced, multi-stage, lossless compression technology.

SCOPE OF DELIVERY

Quantity	Description	Article number
1	USB-AM/BM-2 cable USB 2m	A6300113
2	DVI-D-DL-M/M-2 cable DVI-D 2m	A6300100
2	Audio-M/M-2-ferrite cable 2m	A6300083

DETAILS

VIDEO

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- Use of a monitor profile optimized for the computer module (EDID profile)
- Flexible use of the EDID data of the workplace monitor as required
- Resolution up to
1920 × 1200 @ 60 Hz,
1280 × 1024 @ 85 Hz

SIGNALS

- Bidirectional audio signals (stereo)

TRANSMISSION

- The transmission distance is up to 140 meters over CAT

DEVICE

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)
- PowerPack not included in the scope of delivery for Basic variants
- UC variant: computer module with two transmission lines for redundancy
 - These modules can be connected to various counterparts, such as compatible console modules or KVM matrix switches
- MultiChannel variants (MC): Modules for multi-monitor workplaces with multi-channel video
 - MC mode uses the full bandwidth for each video channel, whereby a separate transmission line is required for each channel

WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension/guarantee renewal possible

FEATURES

OPERATION FEATURES

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Compatibility with special USB-HID input devices
- Operation via multilingual on-screen display (OSD) and hotkeys
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness

EXTENSIONS

DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply
- Device mounting via RackMount sets, TableMount sets or other mounting tools

SYSTEM EXTENSION

- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.

TECHNICAL DATA

General	Product group	KVM extenders KVM matrix systems
	Number of sources	1
Input options	USB mouse	yes
	USB keyboard	yes
	PS/2 mouse	yes
	PS/2 keyboard	yes
Transmission	Number of transmission channels	2
	Redundant transmission channels	no redundant KVM transmission
	Range	140 m (AWG22) 100 m (AWG24) 80 m (AWG26)
	KVM matrix system component	Computer module
	Medium	CAT5e CAT6 CAT7
	Data rate	1 Gbit/s
Video input	Number of video channels	2
	Format	Singlelink DVI
	Colour depth	24 bit
	Pixel rate	ca. 25 MHz to ca. 165 MHz
	Vertical frequency	50 Hz to 180 Hz

	Horizontal frequency	30 kHz to 130 kHz
	Exemplary resolutions	1920 × 1200 (60 Hz) - Full HD / WUXGA 1920 × 1080 (60 Hz) - Full HD / WUXGA 1600 × 1200 (60 Hz) - Full HD / WUXGA 1280 × 1024 (85 Hz) - Full HD / WUXGA 1280 × 1024 (60 Hz) - Full HD / WUXGA Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.
Audio	Transmission type	Bidirectional Stereo
	Resolutions	24 bit digital
	Sampling rate	up to 96 kHz
	Bandwidth	22 kHz
	Audio support	Analog
Maintenance	Update via	Update Wizard (service interface)
	Serviceport settings	115200bps (8/N/1)
Housing	Material	anodised aluminium
	Width	ca. 105 mm
	Height	ca. 46 mm
	Depth	ca. 104 mm
	IP protection class	IP20
	Weight	ca. 0.41 kg
Operating conditions	Operating temperature	5 °C to 45 °C
	Operating air humidity	20 % to 80 %, non-condensing

	Area of application	Interior
	Maximum operating altitude	3048m above sea level
	Storage temperature	-20 °C to 60 °C
	Storage air humidity	15 % to 85 %, non-condensing
	MTBF	280000 h at 25°C
	Conformities	CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)
Power supply	Input voltage	12 VDC
	Current consumption	0.8 A

MORE VARIANTS

Description	Article number
DVI-CPU 2.0 Basic Computer module to extend DVI signals via CAT cable	A2320070
DVI-CPU 2.0 incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320071
DVI-CPU 3.0 Basic Computer module to extend DVI signals via CAT cable	A2320387
DVI-CPU 3.0 incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320388
DVI-CPU 4.0 Basic Computer module to extend DVI signals via CAT cable	A2320487
DVI-CPU 4.0 incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320488
DVI-CPU-FSC 3.0 Basic Computer module to extend DVI signals via CAT cable	A2320389
DVI-CPU-FSC 3.0 incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320390
DVI-CPU-MC2 2.0 incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320072
DVI-CPU-MC2 3.0 Basic Computer module to extend DVI signals via CAT cable	A2320391
DVI-CPU-MC2 3.0 incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320392
DVI-CPU-UC 2.0 Basic Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320074
DVI-CPU-UC 2.0 incl. PowerPack Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320075
DVI-CPU-UC 3.0 Basic Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320393
DVI-CPU-UC 3.0 incl. PowerPack Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320394

Description	Article number
DVI-CPU-UC 4.0 Basic Computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320489
DVI-CPU-UC 4.0 Incl. PowerPack Computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320490
DVI-CPU-UC-FSC 3.0 Basic Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320395
DVI-CPU-UC-FSC 3.0 Incl. PowerPack Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320396
DVI-U-CPU 3.0 Basic Computer module to extend DVI signals via CAT cable	A2320397
DVI-U-CPU 3.0 Incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320398
DVI-U-CPU 4.0 Basic Computer module to extend DVI signals via CAT cable	A2320491
DVI-U-CPU 4.0 Incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320492
DVI-U-CPU Basic Computer module to extend DVI signals via CAT cable	A2320126
DVI-U-CPU Incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320125
DVI-U-CPU-FSC 3.0 Basic Computer module to extend DVI signals via CAT cable	A2320399
DVI-U-CPU-FSC 3.0 Incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320400
DVI-U-CPU-MC2 3.0 Basic Computer module to extend DVI signals via CAT cable	A2320401
DVI-U-CPU-MC2 3.0 Incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320402
DVI-U-CPU-MC2 Basic Computer module to extend DVI signals via CAT cable	A2320110
DVI-U-CPU-MC2 Incl. PowerPack Computer module to extend DVI signals via CAT cable	A2320109

Description	Article number
DVI-U-CPU-UC 3.0 Basic Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320403
DVI-U-CPU-UC 3.0 incl. PowerPack Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320404
DVI-U-CPU-UC 4.0 Basic Computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320493
DVI-U-CPU-UC 4.0 incl. PowerPack Computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320494
DVI-U-CPU-UC Basic Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320114
DVI-U-CPU-UC incl. PowerPack Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320113
DVI-U-CPU-UC-FSC 3.0 Basic Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320405
DVI-U-CPU-UC-FSC 3.0 incl. PowerPack Splitter computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable	A2320406

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +49 271 23872-333
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung
Obere Leimbach 9 | 57074 Siegen | NRW |
Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Guntermann & Drunck GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales.me@gdsys.com

APAC OFFICE

Guntermann & Drunck GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales.apac@gdsys.com