

# DVI-CPU-UC 4.0 INCL. POWERPACK

KVM extenders, Article number A2320490



The matrix-compatible KVM extenders of the DVI-CPU series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated CAT or fiber connection (up to 10,000 m). An extender system consists of a computer module (CPU) and a compatible console module (CON). Computers can be controlled in near real-time – both in extender and matrix applications. The DVI-CPU series supports SingleLink DVI for digital video resolutions up to 1920 x 1200 (60 Hz). Video data is processed pixel-perfectly and offers excellent hand-eye coordination, thanks to bluedec™ – G&D's advanced, multi-stage, lossless compression technology.

## SCOPE OF DELIVERY

| Quantity | Description                             | Article number |
|----------|---|----------------|
| 1        | PowerCable-2 Standard cable 2m          | A6300057       |
| 1        | Netzteil 12V / 2,08AFSP025-D12C14 FSP   | Z0005926       |
| 1        | USB-AM/BM-2 cable USB 2m                | A6300113       |
| 1        | DVI-D-DL-M/M-2 cable DVI-D 2m           | A6300100       |
| 2        | Audio-M/M-2-ferrite cable 2m            | A6300083       |
| 1        | Safety instructions flyer - FCC class B | A9100371       |

## DETAILS

### VIDEO

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- Use of a monitor profile optimized for the computer module (EDID profile)
- Flexible use of the EDID data of the workplace monitor as required
- Resolution up to  
1920 × 1200 @ 60 Hz,  
1280 × 1024 @ 85 Hz

### SIGNALS

- Bidirectional audio signals (stereo)

### TRANSMISSION

- The transmission distance is up to 140 meters over CAT

### DEVICE

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)
- PowerPack not included in the scope of delivery for Basic variants
- UC variant: computer module with two transmission lines for redundancy
  - These modules can be connected to various counterparts, such as compatible console modules or KVM matrix switches
- MultiChannel variants (MC): Modules for multi-monitor workplaces with multi-channel video
  - MC mode uses the full bandwidth for each video channel, whereby a separate transmission line is required for each channel

### WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

## FEATURES

### OPERATION FEATURES

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Compatibility with special USB-HID input devices
- Operation via multilingual on-screen display (OSD) and hotkeys
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness

## EXTENSIONS

### DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply
- Device mounting via RackMount sets, TableMount sets or other mounting tools

### SYSTEM EXTENSION

- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.

## TECHNICAL DATA

|               |                                 |  |
|---------------|---------------------------------|--|
| General       | Product group                   | KVM extenders                                  |
|               | Product Family                  | MTX-CPU/CON                                    |
|               | Number of sources               | 1  |
|               | KVM matrix system component     | Computer module (digital)                      |
|               | Power Supply                    | no redundancy                                  |
| Input options | USB mouse                       | yes  |
|               | USB keyboard                    | yes  |
|               | PS/2 mouse                      | yes  |
|               | PS/2 keyboard                   | yes  |
| Transmission  | Number of transmission channels | 1  |
|               | Redundant transmission channels | Redundant KVM transmission available           |
|               | Range                           | 140 m (AWG22)<br>100 m (AWG24)<br>80 m (AWG26) |
|               | Medium                          | CAT5e<br>CAT6<br>CAT7                          |
|               | Data rate                       | 1 Gbit/s                                       |
| Video input   | Quantity                        | 1  |
|               | Format                          | Singlelink DVI                                 |
|               | Colour depth                    | 24 bit   |

|             |                       |   |
|-------------|-----------------------|---|
|             | Pixel rate ca.        | 25 MHz to 165 MHz   |
|             | Vertical frequency    | 50 Hz to 180 Hz   |
|             | Horizontal frequency  | 30 kHz to 130 kHz   |
|             | Exemplary resolutions | 1920 x 1200 (60 Hz)<br>1920 x 1080 (60 Hz)<br>1600 x 1200 (60 Hz)<br>1280 x 1024 (85 Hz)<br>1280 x 1024 (60 Hz) |
|             | General Notes         | Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.     |
| Audio       | Transmission type     | Bidirectional<br>Stereo   |
|             | Resolutions           | 24 bit digital  |
|             | Sampling rate         | up to 96 kHz  |
|             | Bandwidth             | 22 kHz  |
|             | Audio support         | Analog  |
| Maintenance | Update via            | Update Wizard (service interface)   |
|             | Serviceport settings  | 115200bps (8/N/1)   |
| Housing     | Material              | Anodised aluminium  |
|             | Width ca.             | 105 mm  |
|             | Height ca.            | 26 mm   |
|             | Depth ca.             | 104 mm  |
|             | IP protection class   | IP20  |

|                      |  |   |
|----------------------|--|---|
|                      | Weight ca.                                 | 0.27 kg   |
| Operating conditions | Operating environment temperature          | 5 °C to 45 °C   |
|                      | Operating air humidity, non-condensing     | 20 % to 80 %  |
|                      | Area of application                        | Indoor use  |
|                      | Maximum operating altitude above sea level | 3,048 m   |
|                      | Storage environment temperature            | -20 °C to 60 °C   |
|                      | Storage air humidity, non-condensing       | 15 % to 85 %  |
|                      | MTBF                                       | 280,000 h at 25°C   |
|                      | Conformities                               | CE compliant (see downloads)<br>UKCA compliant (see downloads)<br>FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads) |
| Power supply         | Quantity                                   | 1   |
|                      | Type                                       | External  |
|                      | Input voltage                              | 12 VDC  |
|                      | Current consumption                        | 0.6 A   |

## ACCESSORY PRODUCTS

| Image   | Description   | Article number |
|---|---|----------------|
|    | <b>USB-Service-2 cable 2m</b><br>Cable for system updates and configuration   | A6200103       |
|    | <b>Audio-M/M-3-ferrite cable 3m</b><br>Audio connection cable with ferrite core   | A6300118       |
|    | <b>Audio-M/M-5-ferrite cable 5m</b><br>Audio connection cable with ferrite core   | A6300085       |
|    | <b>DVI-D-DL-M/M-3 cable DVI-D 3m</b><br>Single cable for connecting a digital dual-link video channel                             | A6300164       |
|    | <b>DVI-D-DL-M/M-5 cable DVI-D 5m</b><br>Single cable for connecting a digital dual-link video channel                             | A6300104       |
|  | <b>USB-AM/BM-3 cable USB 3m</b><br>USB cable, Type-A Plug/Type-B Plug   | A6300114       |
|  | <b>USB-AM/BM-5 cable USB 5m</b><br>USB cable, Type-A Plug/Type-B Plug   | A6300111       |
|  | <b>CaseMount-Set-105-26 mounting bracket</b><br>Screws & brackets for mounting devices with dimensions 105x26mm in DeviceCarriers | A7000020       |

## MORE VARIANTS

| Description   | Article number |
|---|----------------|
| <b>DVI-CPU 3.0 Basic</b><br>Computer module to extend DVI signals via CAT cable   | A2320387       |
| <b>DVI-CPU 3.0 incl. PowerPack</b><br>Computer module to extend DVI signals via CAT cable   | A2320388       |
| <b>DVI-CPU 4.0 Basic</b><br>Computer module to extend DVI signals via CAT cable   | A2320487       |
| <b>DVI-CPU 4.0 incl. PowerPack</b><br>Computer module to extend DVI signals via CAT cable   | A2320488       |
| <b>DVI-CPU-MC2 3.0 Basic</b><br>Computer module to extend DVI signals via CAT cable   | A2320391       |
| <b>DVI-CPU-MC2 3.0 incl. PowerPack</b><br>Computer module to extend DVI signals via CAT cable   | A2320392       |
| <b>DVI-CPU-UC 4.0 Basic</b><br>Computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable             | A2320489       |
| <b>DVI-U-CPU 3.0 Basic</b><br>Computer module to extend DVI signals via CAT cable   | A2320397       |
| <b>DVI-U-CPU 3.0 incl. PowerPack</b><br>Computer module to extend DVI signals via CAT cable   | A2320398       |
| <b>DVI-U-CPU 4.0 Basic</b><br>Computer module to extend DVI signals via CAT cable   | A2320491       |
| <b>DVI-U-CPU 4.0 incl. PowerPack</b><br>Computer module to extend DVI signals via CAT cable   | A2320492       |
| <b>DVI-U-CPU-MC2 3.0 Basic</b><br>Computer module to extend DVI signals via CAT cable   | A2320401       |
| <b>DVI-U-CPU-MC2 3.0 incl. PowerPack</b><br>Computer module to extend DVI signals via CAT cable   | A2320402       |
| <b>DVI-U-CPU-UC 4.0 Basic</b><br>Computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable           | A2320493       |
| <b>DVI-U-CPU-UC 4.0 incl. PowerPack</b><br>Computer module for transmission of DVI signals to 2 different counterpart stations (extenders or matrix switches) via CAT cable | A2320494       |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +49 271 23872-333  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)