



# U2+R-FIBER(S+)-CON

KVM extenders, Article number A1120355



The U2+R-CON console module transmits USB2.0 high-speed and RS232 signals from a console to a compatible computer module of the U2+R series.

## SCOPE OF DELIVERY

| Quantity | Description                    | Article number |
|----------|--------------------------------|----------------|
| 1        | PowerCable-2 Standard cable 2m | A6300057       |

## DETAILS

### SIGNALS

- Transparent RS232 (max. 115,200 bps)
- Embedded USB 2.0 with Hi-Speed, transparent, all USB classes

### TRANSMISSION

- The transmission distance is up to 10,000 meters over fiber singlemode+ optics, incl. transmission module(s)/ SFP transceiver(s)

### DEVICE

- PowerPack not included in the scope of delivery for Basic variants

### WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension/guarantee renewal possible

## FEATURES

### SIGNALS

- The serial interface can also be configured for RS422 transmission.

## EXTENSIONS

### DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply

## TECHNICAL DATA

|              |                                 |                                     |
|--------------|---------------------------------|-------------------------------------|
| General      | Product group                   | KVM extenders<br>KVM matrix systems |
|              |                                 |                                     |
| Transmission | Number of transmission channels | 1                                   |
|              | Redundant transmission channels | no redundant KVM transmission       |
|              | Range                           | 10000 m (9/125µm, OS1)              |
|              | Laser class                     | Class 1                             |
|              | Type of interface               | LC-Duplex                           |
|              | Wavelength                      | 1310 nm                             |
|              | KVM matrix system component     | Console module                      |
|              | Medium                          | Fiber SM+                           |
|              | Data rate                       | 2.5 Gbit/s                          |
| USB          | Specification                   | USB 2.0                             |
|              | Medium                          | Embedded                            |
|              | Transmission rate               | 480 Mbit/s (Hi-Speed)               |
|              | Range                           | max. 10000 m                        |
|              | USB classes                     | All                                 |
| Serial       | Standard                        | RS232<br>RS422                      |
|              | Transparent transmission        | yes                                 |
|              | Data rate                       | max. 115200 bps                     |

|                      |                            |                                                                                  |
|----------------------|----------------------------|----------------------------------------------------------------------------------|
|                      | Signals                    | TxD<br>RxD<br>DTR<br>DSR<br>RTS<br>CTS<br>DCD<br>TxA<br>TxB<br>RxB<br>RxA<br>GND |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
|                      |                            |                                                                                  |
| Maintenance          | Update via                 | Update Wizard (service interface)                                                |
|                      | Serviceport settings       | 115200bps (8/N/1)                                                                |
| Housing              | Material                   | anodised aluminium                                                               |
|                      | Width                      | ca. 105 mm                                                                       |
|                      | Height                     | ca. 26 mm                                                                        |
|                      | Depth                      | ca. 104 mm                                                                       |
|                      | IP protection class        | IP20                                                                             |
|                      | Weight                     | ca. 0.27 kg                                                                      |
| Operating conditions | Operating temperature      | 5 °C to 45 °C                                                                    |
|                      | Operating air humidity     | 20 % to 80 %, non-condensing                                                     |
|                      | Area of application        | Interior                                                                         |
|                      | Maximum operating altitude | 3048m above sea level                                                            |
|                      | Storage temperature        | -20 °C to 60 °C                                                                  |
|                      | Storage air humidity       | 15 % to 80 %, non-condensing                                                     |
|                      | MTBF                       | 280000 h at 25°C                                                                 |

|              |                        |                                                                                                                                                                                                                                                                   |
|--------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|              | Conformities           | CE compliant (see downloads)<br>UKCA compliant (see downloads)<br>FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads) |
|              |                        |                                                                                                                                                                                                                                                                   |
| Power supply | Input voltage          | 12 VDC                                                                                                                                                                                                                                                            |
|              | Current consumption    | 1.8 A                                                                                                                                                                                                                                                             |
|              | Power consumption idle | 1.68 W                                                                                                                                                                                                                                                            |
|              | Power consumption max. | 18.48 W                                                                                                                                                                                                                                                           |
|              | Heat output idle       | 1.68 W                                                                                                                                                                                                                                                            |
|              | Heat output max.       | 3.48 W                                                                                                                                                                                                                                                            |



## MORE VARIANTS

| Description                                                                                                    | Article number |
|----------------------------------------------------------------------------------------------------------------|----------------|
| <b>U2-R-CON</b><br>User console for transparent USB2.0 transmission (high-speed) via CAT cable                 | A1120352       |
| <b>U2-R-Fiber(M)-CON</b><br>User console for transparent USB2.0 transmission (high-speed) via fiber multimode  | A1120353       |
| <b>U2-R-Fiber(S)-CON</b><br>User console for transparent USB2.0 transmission (high-speed) via fiber singlemode | A1120354       |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +1-833-928-1976  
Fax: +1-833-928-1976  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)