

**Guntermann & Drunck GmbH Systementwicklung**  
Obere Leimbach 9 | 57074 Siegen | Germany | T +49 271 23872-0 | F +49 271 23872-120 |  
[sales@gdsys.com](mailto:sales@gdsys.com) | [www.gdsys.com](http://www.gdsys.com)

G&D Product data sheet - 29. Oct 2025 [DP1.2-Vision-CAT-AR-CON-2](#)

# DP1.2-Vision-CAT-AR-CON-2

**KVM extenders, Article number A1120301**

Front

Back

The matrix-compatible KVM extenders of the DP1.2-Vision series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated CAT or fiber connection (up to 10,000 m). An extender system consists of a computer module (CPU) and a compatible console module (CON). Computers can be controlled in near real-time – both in extender and matrix applications. The DP1.2-Vision series supports DisplayPort1.2 for ultra-high-resolution video up to  $4096 \times 2160$  (60 Hz) or  $5120 \times 2160$  (50 Hz). Video data is processed pixel-perfectly and offers excellent hand-eye coordination, thanks to bluedec™ – G&D's advanced, multi-stage, lossless compression technology.

## Scope of delivery

| Quantity | Description                    | Article number |
|----------|--------------------------------|----------------|
| 1        | PowerCable-2 Standard cable 2m | A6300057       |

## Details

### Video

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- EDID data utilization from the workplace monitor
- Flexible EDID profile options for optimized monitor settings
- Resolution up to  
 $5120 \times 2160$  @ 50 Hz,  
 $5120 \times 1440$  @ 60 Hz,  
 $4096 \times 2160$  @ 60 Hz,  
 $2560 \times 1440$  @ 144 Hz,  
 $1920 \times 1080$  @ 240 Hz

### Signals

- Transparent audio signals (stereo, analog)
- Embedded stereo audio (Digital, 2 channel LPCM)
- Transparent RS232 (max. 115,200 bps)

### Transmission

- The transmission distance is up to 140 meters over CAT

### Device

- Improved security through physical separation between workplaces and computers

- Access to standard interfaces of the computer, with no software installation required
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)
- Internal power pack for main power supply
- CON-2 variant: console module with two transmission lines for redundancy
  - These modules can be connected to various counterparts, such as compatible computer modules or KVM matrix switches, whereby switching is carried out via pushbuttons, hotkeys or automatically, depending on the configuration
- UC variant: computer module with two transmission lines for redundancy
  - These modules can be connected to various counterparts, such as compatible console modules or KVM matrix switches
- MultiChannel variants (MC): Modules for multi-monitor workplaces with multi-channel video
  - MC mode uses the full bandwidth for each video channel, whereby a separate transmission line is required for each channel

## **Warranty**

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

## **Features**

### **Security features**

- Console modules do not store security-relevant information such as login credentials, which could be extracted in the event of device loss
- Early detection of security incidents or unusual activities through continuous monitoring via Syslog, monitoring, and SNMP
- Comprehensive rights management and user administration, allowing precise control over which user can access which resources
- Option for activatable access protection (default operating mode in matrix systems), in which authentication is required before accessing computer sources
- Support for external directory services (Active Directory, Radius, LDAP) to meet company security policies
- To comply with individual password policies and improve security, password complexity can be configured system-wide
- Configurable login options, such as displaying terms of use or setting the maximum acceptable number of failed login attempts, can enhance system security

- **Auto Backup Function:** Automates backups at user-defined intervals and replaces manual intervention – ensuring reliable, timely data protection without the need for continuous monitoring
- **Freeze function:** If the video signal is lost, the last displayed image is frozen and highlighted with a colored frame and timer
- **2-Factor-Authentication (2FA)** – is integrated by default in KVM extenders and enhances security by requiring a second, possession-based factor during user authentication:
  - The traditional password authentication is combined with a time-limited, single-use code (Time-Based-One-Time-Password - TOTP)
  - You can choose between using the internal authentication server provided in the device or an external directory service
  - Authenticator apps or hardware token can be used
  - This additional layer of protection prevents unauthorized access and ensures the highest level of security, particularly in sensitive IT environments

## Operation features

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Compatibility with special USB-HID input devices
- Operation via multilingual on-screen display (OSD) and hotkeys
- Configuration and update via the multilingual HTML5 web interface “Config Panel 21” (Java-free)
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness
- Local console at the computer module allows on-site operation, including all video channels
- **Exclusive or concurrent operation:** The KVM extender allows computer control both remotely and locally. When an input is detected, the extender automatically locks the competing console. The lock is lifted after a preset timeout if no further input is detected. A key combination can activate exclusive operation, immediately disabling the competing console. Another key combination restores shared control.

## Extensions

### Device


- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply
- Device mounting via RackMount sets, TableMount sets or other mounting tools

# System extension

- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.


# Interfaces

## Front



| Aperture designation | Design           | Description                  |
|----------------------|------------------|------------------------------|
| Transmission 1       | Button           | Button for channel switching |
| Transmission 2       | Button           | Button for channel switching |
| Network              | RJ45 socket      | Port for IP network          |
| Service              | Micro-USB socket | Port for service purposes    |

## Back



| Aperture designation | Design               | Description                                                 |
|----------------------|----------------------|-------------------------------------------------------------|
| Transmission 2       | RJ45 socket          | Data transmission to computer module or matrix switch (CAT) |
| Transmission 1       | RJ45 socket          | Data transmission to computer module or matrix switch (CAT) |
| DP Out               | DisplayPort socket   | Port for monitor                                            |
| Line In              | Jack socket - 3,5 mm | Port for microphone / audio source                          |
| Speaker              | Jack socket - 3,5 mm | Port for speaker/headset                                    |
| Generic              | USB-A socket 2.0     | Port for USB devices (Generic)                              |
| Keyb./Mouse          | USB-A socket 2.0     | Port for keyboard and mouse                                 |
| Keyb./Mouse          | USB-A socket 2.0     | Port for keyboard and mouse                                 |

| Aperture designation | Design            | Description                 |
|----------------------|-------------------|-----------------------------|
| Keyb./Mouse          | PS/2 socket       | Port for keyboard and mouse |
| RS232                | D-Sub9 socket     | Port for serial devices     |
| Red. Power 12VDC     | Mini-DIN 4 socket | Power supply DC redundant   |
| Main Power           | IEC plug 320 C14  | Power supply AC             |

## Technical data

|                      |                                 |                                                                |
|----------------------|---------------------------------|----------------------------------------------------------------|
| General              | Product group                   | KVM extenders                                                  |
|                      | Product Family                  | Vision                                                         |
|                      | Number of workstations          | 1                                                              |
|                      | KVM matrix system component     | Console module (digital)                                       |
|                      | Power Supply                    | Redundancy without load balancing                              |
| Input options        | USB mouse                       | yes                                                            |
|                      | USB keyboard                    | yes                                                            |
|                      | PS/2 mouse                      | no                                                             |
|                      | PS/2 keyboard                   | yes                                                            |
| Transmission         | Number of transmission channels | 1                                                              |
|                      | Redundant transmission channels | Redundant KVM transmission available                           |
|                      | Range                           | 140 m (AWG22)                                                  |
|                      |                                 | 100 m (AWG24)                                                  |
|                      |                                 | 80 m (AWG26)                                                   |
| Medium               | CAT5e                           |                                                                |
|                      | CAT6                            |                                                                |
|                      | CAT7                            |                                                                |
|                      | Data rate                       | 1 Gbit/s                                                       |
|                      | Quantity                        | 1                                                              |
|                      | Format                          | DisplayPort 1.2 (LBR, HBR, HBR2, SingleStream-Transport (SST)) |
|                      | Colour depth                    | 24 bit                                                         |
|                      | Pixel encoding                  | RGB 4:4:4 (24 bpp / 8 bpc)                                     |
|                      | Pixel rate ca.                  | 25 MPixel/s to 600 MPixel/s                                    |
| Video output         | Vertical frequency              | 24 Hz to 240 Hz                                                |
|                      | Horizontal frequency            | 25 kHz to 295 kHz                                              |
|                      | Exemplary resolutions           | 4096 × 2160 (60 Hz)                                            |
|                      |                                 | 3840 × 2160 (60 Hz)                                            |
|                      |                                 | 2560 × 1600 (60 Hz)                                            |
|                      |                                 | 2560 × 1440 (144 Hz)                                           |
|                      |                                 | 2048 × 2048 (60 Hz)                                            |
|                      |                                 | 1920 × 1200 (60 Hz)                                            |
| 1920 × 1080 (240 Hz) |                                 |                                                                |

|                    |                              |                                                                                                             |
|--------------------|------------------------------|-------------------------------------------------------------------------------------------------------------|
| <b>Audio 1</b>     | General Notes                | 1920 × 1080 (60 Hz)                                                                                         |
|                    |                              | 5120 × 1440 (60 Hz)                                                                                         |
|                    |                              | 5120 × 2160 (50 Hz)                                                                                         |
|                    | General Notes                | Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency. |
|                    | Supported industry standards | Display Data Channel Command Interface (DDC/CI)<br>Extended Display Identification Data (EDID)              |
|                    | Transmission type            | Stereo<br>Transparent                                                                                       |
|                    | Resolutions                  | 24 bit digital                                                                                              |
| <b>Audio 2</b>     | Sampling rate                | up to 96 kHz                                                                                                |
|                    | Bandwidth                    | 22 kHz                                                                                                      |
|                    | Audio support                | Analog                                                                                                      |
|                    | Transmission type            | Stereo<br>2-channel LPCM                                                                                    |
|                    | Resolutions                  | 24 bit<br>20 bit<br>16 bit                                                                                  |
|                    | Sampling rate                | up to 48 kHz                                                                                                |
|                    | Audio support                | Digital Embedded                                                                                            |
| <b>Serial</b>      | Standard                     | RS232                                                                                                       |
|                    | Transparent transmission     | yes                                                                                                         |
|                    | Data rate                    | max. 115,200 bps                                                                                            |
|                    | Signals                      | TxD                                                                                                         |
|                    |                              | RxD                                                                                                         |
|                    |                              | DTR                                                                                                         |
|                    |                              | DSR                                                                                                         |
|                    |                              | RTS                                                                                                         |
| <b>Network</b>     | Medium                       | CTS                                                                                                         |
|                    |                              | DCD                                                                                                         |
|                    |                              | Quantity                                                                                                    |
|                    | Quantity                     | 1                                                                                                           |
| <b>Maintenance</b> | Update via                   | CAT5                                                                                                        |
|                    |                              | CAT6                                                                                                        |
|                    |                              | CAT7                                                                                                        |
|                    | Serviceport settings         | 10 Mbit/s<br>100 Mbit/s                                                                                     |
| <b>Housing</b>     | Material                     | ConfigPanel (Network)                                                                                       |
|                    | Width ca.                    | 115200bps (8/N/1)                                                                                           |
|                    | Height ca.                   | anodised aluminium                                                                                          |
|                    | Depth ca.                    | 210 mm                                                                                                      |
|                    | IP protection class          | 44 mm                                                                                                       |
|                    | Weight ca.                   | 210 mm                                                                                                      |
|                    |                              | IP20                                                                                                        |
|                    |                              | 1.33 kg                                                                                                     |

|                             |                                            |                                 |
|-----------------------------|--------------------------------------------|---------------------------------|
| <b>Operating conditions</b> | Operating temperature                      | 5 °C to 45 °C                   |
|                             | Operating air humidity, non-condensing     | 20 % to 80 %                    |
|                             | Area of application                        | Indoor use                      |
|                             | Maximum operating altitude above sea level | 3,048 m                         |
|                             | Storage temperature                        | -20 °C to 55 °C                 |
|                             | Storage air humidity, non-condensing       | 15 % to 85 %                    |
|                             | MTBF                                       | 140,000 h at 25°C               |
|                             | Conformities                               | CE compliant (see downloads)    |
|                             |                                            | UKCA compliant (see downloads)  |
|                             |                                            | UL compliant (see downloads)    |
|                             |                                            | CB compliant (see downloads)    |
|                             |                                            | FCC compliant (see manual)      |
|                             |                                            | TAA compliant (see downloads)   |
|                             |                                            | EAC compliant (see downloads)   |
|                             |                                            | RoHS compliant (see downloads)  |
|                             |                                            | WEEE (reg. no. DE30763240)      |
|                             |                                            | REACH compliant (see downloads) |
| <b>Power supply 1</b>       | Quantity                                   | 1                               |
|                             | Type                                       | Internal                        |
|                             | Input voltage                              | 100-240 VAC                     |
|                             | Input frequency                            | 60-50 Hz                        |
|                             | Current consumption                        | 0.6-0.3 A                       |
|                             | Power consumption max.                     | 25.4 W                          |
|                             | Heat output max.                           | 17.4 W                          |
|                             | Quantity                                   | 1                               |
| <b>Power supply 2</b>       | Type                                       | External                        |
|                             | Input voltage                              | 12 VDC                          |
|                             | Current consumption                        | 2 A                             |
|                             | Power consumption max.                     | 23.6 W                          |
|                             | Heat output max.                           | 15.6 W                          |

accessory products

| Image | Description                                                                             | Article number |
|-------|-----------------------------------------------------------------------------------------|----------------|
|       | <b>USB-Service-2 cable 2m</b><br>Cable for system updates and configuration             | A6200103       |
|       | <b>PowerCable-3 Standard cable 3m</b><br>Cable to connect the power supply type Germany | A6300066       |

| Image | Description                                                                                                    | Article number |
|-------|----------------------------------------------------------------------------------------------------------------|----------------|
|       | <b>PowerCable-5 Standard cable 5m</b><br>Cable to connect the power supply type Germany                        | A6300065       |
|       | <b>19" RM-Set-210-1RU</b><br>19" extension for rack mounting devices of 210 mm width within 1RU (44 mm height) | A7000022       |
|       | <b>PowerPack 12 Type 3 12V/2A</b><br>24W power supply with 2m powercable                                       | A4110013       |

## related products

| Description                                                                                        | Article number |
|----------------------------------------------------------------------------------------------------|----------------|
| <b>TS-LED-blue-R-2</b><br>LED to tag the active console of a TradeSwitch configuration of a matrix | A6100173       |
| <b>TS-LED-blue-R-3</b><br>LED to tag the active console of a TradeSwitch configuration of a matrix | A6100172       |
| <b>TS-LED-blue-R-5</b><br>LED to tag the active console of a TradeSwitch configuration of a matrix | A6100171       |

## more variants

| Description                                                                                                                | Article number |
|----------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>DP1.2-Vision-CAT-AR-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                           | A1120300       |
| <b>DP1.2-Vision-CAT-ARU-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                          | A1120302       |
| <b>DP1.2-Vision-CAT-ARU-CON-2</b><br>Redundant console module to receive DisplayPort1.2 signals of 2 sources via CAT cable | A1120303       |
| <b>DP1.2-Vision-CAT-ARU2-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                         | A1120304       |
| <b>DP1.2-Vision-CAT-MC2-AR-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                       | A1220240       |
| <b>DP1.2-Vision-CAT-MC2-ARU-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                      | A1220241       |
| <b>DP1.2-Vision-CAT-MC2-ARU2-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                     | A1220242       |
| <b>DP1.2-Vision-CAT-MC3-AR-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                       | A1320023       |
| <b>DP1.2-Vision-CAT-MC3-ARU-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                      | A1320024       |
| <b>DP1.2-Vision-CAT-MC3-ARU2-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                     | A1320025       |
| <b>DP1.2-Vision-CAT-MC4-AR-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                       | A1420244       |
| <b>DP1.2-Vision-CAT-MC4-ARU-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                      | A1420245       |
| <b>DP1.2-Vision-CAT-MC4-ARU2-CON</b><br>Console module to receive DisplayPort1.2 signals via CAT cable                     | A1420246       |

# Contact

## We are here for you!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### Technical sales

Tel.: +49 271 23872-333  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### Headquarters

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW | Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### Middle East office

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)