

VISIONVS-FIBER(S)

KVM extenders, Article number A1110805



Front



Back

The VisionVS is a hybrid computer module featuring a dual encoder that transmits KVM signals with virtually zero latency and lossless quality via a dedicated G&D KVM matrix to the workplace. At the same time, it enables remote access to the computer via web interface or low-latency streaming to VuWall PAK devices for flexible video wall management.

SCOPE OF DELIVERY

Quantity	Description	Article number
1	PowerCable-2 Standard cable 2m	A6300057
1	USB-AM/BM-2 cable USB 2m	A6300113
1	DP1.4-Cable-M/M-2 SK13357 2m	A6300173

DETAILS

VIDEO

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- Resolution up to
2560 × 1600 @ 60 Hz,
4096 × 2160 @ 30 Hz
- Resolution up to
2560 × 1600 @ 60 Hz,
4096 × 2160 @ 30 Hz

SIGNALS

- Embedded stereo audio (2 channel LPCM)

TRANSMISSION

- The transmission distance is up to 5,000 meters over fiber singlemode optics, incl. transmission module(s)/SFP transceiver(s)

DEVICE

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)
- Internal power pack for main power supply

FEATURES

OPERATION FEATURES

- Video wall processing and KVM combined in one appliance
The combination of powerful image processing and KVM functionality reduces the number of required devices.
- Direct streaming to G&D KVM matrix systems and VuWall PAK nodes
Flexible use in hybrid environments with both centralized and decentralized access to computing resources.
- Reduced system complexity, lower cabling effort, and minimal rack space requirements
A more efficient infrastructure with fewer hardware components saves costs, conserves space, and simplifies installation.

EXTENSIONS

TRANSMISSION

- A VuWall TRx appliance with version 3.11 or higher is required for the VuWall streaming application.

DEVICE


- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply

SYSTEM EXTENSION

- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.


INTERFACES

FRONT



Aperture designation	Design	Description
Network Management	RJ45 socket	Port for IP network
Service	Mini-USB socket	Port for service purposes

BACK



Aperture designation	Design	Description
HDMI Out	HDMI socket	Port for monitor
USB K/M	USB-A socket 2.0	Port for keyboard and mouse
Control	Clamp block - 5 pins	Port for external remote control
Network	RJ45 socket	Port for IP network
Transmission	SC-Duplex socket	Data transmission to console module or matrix switch (FIBER)
DisplayPort CPU	DisplayPort socket	Connection to computer - Video
USB CPU	USB-B socket 2.0	Connection to computer - USB
Red. Power 12VDC	Mini-DIN 4 socket	Power supply DC redundant
Main Power	IEC plug 320 C14	Power supply AC

TECHNICAL DATA

General	Product group	KVM extenders KVM matrix systems
Input options	USB mouse	yes
	USB keyboard	yes
Transmission	Number of transmission channels	1
	Redundant transmission channels	no redundant KVM transmission
	Range	5000 m (9/125µm, OS1)
	Laser class	Class 1
	Type of interface	LC-Duplex
	Wavelength	1310 nm
	KVM matrix system component	Computer module
	Medium	Fiber SM
	Data rate	2.5 Gbit/s
Video input	Number of video channels	1
	Format	DisplayPort 1.1 (HBR)
	Colour depth	24 bit
	Pixel rate	ca. 25 MPixel/s to ca. 300 MPixel/s
	Vertical frequency	24 Hz to 120 Hz
	Horizontal frequency	25 kHz to 185 kHz

	Exemplary resolutions	4096 × 2160 (30 Hz) - 2K / WQXGA 4096 × 2160 (25 Hz) - 2K / WQXGA 4096 × 2160 (24 Hz) - 2K / WQXGA 3840 × 2160 (30 Hz) - 2K / WQXGA 3840 × 2160 (25 Hz) - 2K / WQXGA 3840 × 2160 (24 Hz) - 2K / WQXGA 2560 × 1600 (60 Hz) - 2K / WQXGA 2048 × 2048 (60 Hz) - 2K / WQXGA 1920 × 1200 (60 Hz) - Full HD / WUXGA 1920 × 1080 (60 Hz) - Full HD / WUXGA Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.
	Supported industry standards	Display Data Channel Command Interface (DDC/CI) Extended Display Identification Data (EDID)
Video output	Number of video channels	1
	Format	HDMI 1.4
	Colour depth	24 bit
	Pixel rate	ca. 25 MPixel/s to ca. 297 MPixel/s
	Exemplary resolutions	4096 × 2160 (24 Hz) - 2K / WQXGA 4096 × 2160 (25 Hz) - 2K / WQXGA 4096 × 2160 (30 Hz) - 2K / WQXGA 3840 × 2160 (24 Hz) - 2K / WQXGA 3840 × 2160 (25 Hz) - 2K / WQXGA 3840 × 2160 (30 Hz) - 2K / WQXGA 2048 × 2160 (60 Hz) - 2K / WQXGA 2048 × 2048 (60 Hz) - 2K / WQXGA 2560 × 1600 (60 Hz) - 2K / WQXGA 1920 × 1200 (60 Hz) - Full HD / WUXGA 1920 × 1080 (60 Hz) - Full HD / WUXGA Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.
Audio	Transmission type	Stereo 2-channel LPCM

	Resolutions	16 bit
	Sampling rate	up to 48 kHz
	Audio support	Digital Embedded
Network	Medium 1	CAT5 CAT6 CAT7
	Data rate 1	10 MBit/s 100 MBit/s
Network 2	Medium 1	CAT5 CAT6 CAT7
	Data rate 1	1 GBit/s 100 MBit/s 10 MBit/s
Maintenance	Update via	WebIF (Network)
Housing	Material	anodised aluminium
	Width	ca. 436 mm
	Height	ca. 44 mm
	Depth	ca. 284 mm
	IP protection class	IP20
Operating conditions	Operating temperature	5 °C to 45 °C
	Operating air humidity	20 % to 80 %, non-condensing
	Area of application	Interior
	Maximum operating altitude	3048m above sea level

	Storage temperature	-20 °C to 60 °C
	Storage air humidity	15 % to 85 %, non-condensing
Power supply	Input voltage	100-240 VAC
	Input frequency	60-50 Hz
Power supply 2	Input voltage	12 VDC

MORE VARIANTS

Description	Article number
VisionVS-CAT Hybrid computer module to extend DisplayPort signals with G&D KVM matrix (CAT) and simultaneous streaming (CAT)	A1110803
VisionVS-Fiber(M) Hybrid computer module to extend DisplayPort signals with G&D KVM matrix (fiber) and simultaneous streaming (CAT)	A1110804
VisionVS-Fiber(S+) Hybrid computer module to extend DisplayPort signals with G&D KVM matrix (fiber) and simultaneous streaming (CAT)	A1110806

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +49 271 23872-333
 Fax: +49 271 23872-120
 E-Mail: sales@gdsys.com

HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung
 Obere Leimbach 9 | 57074 Siegen | NRW |
 Deutschland

Tel.: +49 271 23872-0
 Fax: +49 271 23872-120
 E-Mail: sales@gdsys.com

US OFFICE

G&D North America Inc.
 4540 Kendrick Plaza Drive | Suite 100
 Houston, TX 77032 | United States

Tel.: +1-346-620-4362
 E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Guntermann & Drunck GmbH
 Dubai Studio City | DSC Tower
 12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
 E-Mail: sales.me@gdsys.com

APAC OFFICE

Guntermann & Drunck GmbH
 60 Anson Road #17-01
 Singapore 079914

Tel.: +65 9685 8807
 E-Mail: sales.apac@gdsys.com