

# VISIONXS-CPU-C-DVI-I-AR-DT

KVM extenders, Article number A1110643



Front



Back

The matrix-compatible KVM extenders of the VisionXS-DVI-I series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated CAT or fiber connection (up to 10,000 m). An extender system consists of a computer module (CPU) and a compatible console module (CON). Computers can be controlled in near real-time – both in extender and matrix applications. The VisionXS-DVI-I series supports SingleLink DVI-I for analog and digital video resolutions up to 1920 x 1200 (60 Hz). Video data is processed pixel-perfectly and offers excellent hand-eye coordination, thanks to bluedec™ – G&D's advanced, multi-stage, lossless compression technology.

## SCOPE OF DELIVERY

| Quantity | Description                      | Article number |
|----------|----------------------------------|----------------|
| 1        | PowerCable-2 Standard cable 2m   | A6300057       |
| 1        | DVI-D-DL-M/M-2 cable DVI-D 2m    | A6300100       |
| 1        | VGA-M/DVI-A-M-2 cable VGA-DVI 2m | A6300053       |
| 1        | USB-AM/BM-2 cable USB 2m         | A6300113       |
| 1        | Audio-M/M-2-ferrite cable 2m     | A6300083       |
| 1        | RS232-M/F-2 cable RS232 2m       | A6300023       |

## DETAILS

### VIDEO

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- EDID data utilization from the workplace monitor
- Flexible EDID profile options for optimized monitor settings
- Resolution up to  
1920 × 1200 @ 60 Hz,  
1280 × 1024 @ 85 Hz

### SIGNALS

- Transparent audio signals (stereo, analog)
- Transparent RS232 (max. 115,200 bps)
- GenericUSB support for USB classes HID (Human Interface Device), SmartCard and mass storage
- The product allows the use of a GenericUSB device via a console module. For this, both the used console module and the used computer module must support the use of a GenericUSB device.

### TRANSMISSION

- The transmission distance is up to 140 meters over CAT

### DEVICE

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- Compact design for space-saving installation within a VisionXS DeviceCarrier (1 or 3 RU)
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)
- PowerPack not included in the scope of delivery
- DT variant: Optional redundant power supply via an internal power unit for high reliability
- Fanless variant: fanless model

### WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension/guarantee renewal possible

## FEATURES

### SECURITY FEATURES

- Bootloader, operating system, and firmware form a "Trusted Computing Platform" with automatic integrity checks during system startup
- Integrated Trusted Platform Module (TPM) protects all access and configuration data from being spied on or tampered with by third parties
- Console modules do not store security-relevant information such as login credentials, which could be extracted in the event of device loss
- Early detection of security incidents or unusual activities through continuous monitoring via Syslog, monitoring, and SNMP
- Comprehensive rights management and user administration, allowing precise control over which user can access which resources
- Option for activatable access protection (default operating mode in matrix systems), in which authentication is required before accessing computer sources
- Support for external directory services (Active Directory, Radius, LDAP) to meet company security policies
- To comply with individual password policies and improve security, password complexity can be configured system-wide
- Configurable login options, such as displaying terms of use or setting the maximum acceptable number of failed login attempts, can enhance system security
- Auto Backup Function: Automates backups at user-defined intervals and replaces manual intervention – ensuring reliable, timely data protection without the need for continuous monitoring
- Freeze function: If the video signal is lost, the last displayed image is frozen and highlighted with a colored frame and timer
- 2-Factor-Authentication (2FA) – is integrated by default in KVM extenders and enhances security by requiring a second, possession-based factor during user authentication:
  - The traditional password authentication is combined with a time-limited, single-use code (Time-Based-One-Time-Password - TOTP)
  - You can choose between using the internal authentication server provided in the device or an external directory service
  - Authenticator apps or hardware token can be used
  - This additional layer of protection prevents unauthorized access and ensures the highest level of security, particularly in sensitive IT environments

### OPERATION FEATURES

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Compatibility with special USB-HID input devices

- Operation via multilingual on-screen display (OSD) and hotkeys
- Configuration and update via the multilingual HTML5 web interface “Config Panel 21” (Java-free)
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness

## EXTENSIONS

### DEVICE


- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply
- Device mounting via G&D 19" DeviceCarrier for VisionXS (1 or 3 RU)

### SYSTEM EXTENSION

- Transm. Redundancy Option (comparable to UC/CON-2): Devices are prepared for transmission redundancy without additional hardware and can be activated via software feature key.
  - Computer modules can connect to various counterparts, such as compatible console modules or KVM matrix switches
  - Console modules can connect to different counterparts, such as compatible computer modules or KVM matrix switches, with switching controlled via hotkey or automatically depending on configuration
  - U2 variants do not support the Transm. Redundancy Option as the 2nd transmission interface is used for the transmission of USB 2.0 data
- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.


## INTERFACES

### FRONT



| Aperture designation | Design               | Description                          |
|----------------------|----------------------|--------------------------------------|
| Line In              | Jack socket - 3,5 mm | Connection to computer - audio       |
| Serial               | D-Sub9 jack          | Connection to computer - serial data |
| USB CPU              | USB-B socket 2.0     | Connection to computer - USB         |
| DVI / VGA CPU        | DVI-I socket         | Connection to computer - Video       |

### BACK



| Aperture designation | Design            | Description                                                          |
|----------------------|-------------------|----------------------------------------------------------------------|
| Transmission 1       | RJ45 socket       | Data transmission to console module or matrix switch (CAT)           |
| Transmission 2       | RJ45 socket       | Data transmission to console module or matrix switch redundant (CAT) |
| Service              | Micro-USB socket  | Port for service purposes                                            |
| Network              | RJ45 socket       | Port for IP network                                                  |
| Main Power           | Mini-DIN 4 socket | Power supply DC                                                      |
| Red. Power           | IEC plug 320 C14  | Power supply AC redundant                                            |

## TECHNICAL DATA

|              |                                 |                                                                                                                                                                                                                                 |
|--------------|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General      | Product group                   | KVM extenders<br>KVM matrix systems                                                                                                                                                                                             |
|              |                                 |                                                                                                                                                                                                                                 |
| Transmission | Number of transmission channels | 1                                                                                                                                                                                                                               |
|              | Redundant transmission channels | optional redundant KVM transmission                                                                                                                                                                                             |
|              | Range                           | 140 m (AWG22)<br>100 m (AWG24)<br>80 m (AWG26)                                                                                                                                                                                  |
|              | KVM matrix system component     | Computer module                                                                                                                                                                                                                 |
|              | Medium                          | CAT5e<br>CAT6<br>CAT7                                                                                                                                                                                                           |
|              | Data rate                       | 1 Gbit/s                                                                                                                                                                                                                        |
|              |                                 |                                                                                                                                                                                                                                 |
| Video input  | Number of video channels        | 1                                                                                                                                                                                                                               |
|              | Format                          | Singlelink DVI                                                                                                                                                                                                                  |
|              | Colour depth                    | 24 bit                                                                                                                                                                                                                          |
|              | Pixel rate                      | ca. 25 MHz to ca. 165 MHz                                                                                                                                                                                                       |
|              | Vertical frequency              | 24 Hz to 120 Hz                                                                                                                                                                                                                 |
|              | Horizontal frequency            | 25 kHz to 135 kHz                                                                                                                                                                                                               |
|              | Exemplary resolutions           | 640 × 480 (60 Hz)<br>1600 × 1200 (60 Hz)<br>1920 × 1080 (60 Hz)<br>1920 × 1200 (60 Hz)<br>Further VESA and CTA standardised<br>resolutions possible within video<br>bandwidth/pixel rate and horizontal/<br>vertical frequency. |

|        |                              |                                                                                                                        |
|--------|------------------------------|------------------------------------------------------------------------------------------------------------------------|
|        | Supported industry standards | Display Data Channel (DDC)<br>Enhanced Display Data Channel (E-DDC)<br>Display Data Channel Command Interface (DDC/CI) |
| Audio  | Transmission type            | Stereo<br>Transparent                                                                                                  |
|        | Resolutions                  | 24 bit digital                                                                                                         |
|        | Sampling rate                | up to 96 kHz                                                                                                           |
|        | Bandwidth                    | 22 kHz                                                                                                                 |
|        | Audio support                | Analog                                                                                                                 |
| USB    | Specification                | USB 2.0                                                                                                                |
|        | GenericUSB support           | 1 device                                                                                                               |
|        | Medium                       | Embedded                                                                                                               |
|        | Transmission rate            | 25 Mbit/s (Full Speed)                                                                                                 |
|        | USB classes                  | Mass Storage (MSC / UMS)<br>Human Interface Device (HID)<br>SmartCard                                                  |
| Serial | Standard                     | RS232                                                                                                                  |
|        | Transparent transmission     | yes                                                                                                                    |
|        | Data rate                    | 115200 bps                                                                                                             |
|        | Signals                      | TxD<br>RxD<br>RTS<br>CTS<br>GND<br>5V                                                                                  |

|                      |                            |                              |
|----------------------|----------------------------|------------------------------|
| Network              | Medium 1                   | CAT5<br>CAT6<br>CAT7         |
|                      | Data rate 1                | 10 MBit/s<br>100 MBit/s      |
| Maintenance          | Update via                 | ConfigPanel (Network)        |
|                      | Serviceport settings       | 115200bps (8/N/1)            |
| Housing              | Material                   | anodised aluminium           |
|                      | Width                      | ca. 170 mm                   |
|                      | Height                     | ca. 40 mm                    |
|                      | Depth                      | ca. 184 mm                   |
|                      | IP protection class        | IP20                         |
|                      | Weight                     | ca. 1.24 kg                  |
| Operating conditions | Operating temperature      | 5 °C to 45 °C                |
|                      | Operating air humidity     | 20 % to 80 %, non-condensing |
|                      | Area of application        | Interior                     |
|                      | Maximum operating altitude | 3048m above sea level        |
|                      | Storage temperature        | -20 °C to 60 °C              |
|                      | Storage air humidity       | 15 % to 85 %, non-condensing |
|                      | MTBF                       | 200000 h at 25°C             |

|                |                     |                                                                                                                                                                                                                                                                   |
|----------------|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                | Conformities        | FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads)<br>CE compliant (see downloads)<br>UKCA compliant (see downloads) |
| Power supply   | Input voltage       | 12 VDC                                                                                                                                                                                                                                                            |
|                | Current consumption | 1 A                                                                                                                                                                                                                                                               |
| Power supply 2 | Input voltage       | 100-240 VAC                                                                                                                                                                                                                                                       |
|                | Input frequency     | 60-50 Hz                                                                                                                                                                                                                                                          |
|                | Current consumption | 0.3-0.2 A                                                                                                                                                                                                                                                         |

## MORE VARIANTS

| Description                                                                                   | Article number |
|-----------------------------------------------------------------------------------------------|----------------|
| <b>VisionXS-CPU-C-DVI-I</b><br>Computer module to extend DVI-I signals via CAT cable          | A1110641       |
| <b>VisionXS-CPU-C-DVI-I-A</b><br>Computer module to extend DVI-I signals via CAT cable        | A1110642       |
| <b>VisionXS-CPU-C-DVI-I-A-U</b><br>Computer module to extend DVI-I signals via CAT cable      | A1110646       |
| <b>VisionXS-CPU-C-DVI-I-A-U2</b><br>Computer module to extend DVI-I signals via CAT cable     | A1110647       |
| <b>VisionXS-CPU-C-DVI-I-AR-U-DT</b><br>Computer module to extend DVI-I signals via CAT cable  | A1110645       |
| <b>VisionXS-CPU-C-DVI-I-AR-U2-DT</b><br>Computer module to extend DVI-I signals via CAT cable | A1110644       |
| <b>VisionXS-CPU-C-DVI-I-DT</b><br>Computer module to extend DVI-I signals via CAT cable       | A1110648       |
| <b>VisionXS-CPU-C-DVI-I-U</b><br>Computer module to extend DVI-I signals via CAT cable        | A1110649       |
| <b>VisionXS-CPU-C-DVI-I-U-DT</b><br>Computer module to extend DVI-I signals via CAT cable     | A1110652       |
| <b>VisionXS-CPU-C-DVI-I-U2</b><br>Computer module to extend DVI-I signals via CAT cable       | A1110650       |
| <b>VisionXS-CPU-C-DVI-I-U2-DT</b><br>Computer module to extend DVI-I signals via CAT cable    | A1110651       |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +49 271 23872-333  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)