

**G&D North America Inc.**

4540 Kendrick Plaza | Dr #100 | Houston, TX 77032 | T +1-346-620-4362 | [sales.us@gdsys.com](mailto:sales.us@gdsys.com) | [www.gdsys.com](http://www.gdsys.com)

G&D Product data sheet - Oct 29, 2025 [VisionXS-CPU-F\(S\)-DP-UHR-U-DT](#)

# **VisionXS-CPU-F(S)-DP-UHR-U-DT**

**KVM extenders, Article number A1110327**

Front

Back

The matrix-compatible KVM extenders of the VisionXS-DP-UHR series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated CAT or fiber connection (up to 10,000 m). An extender system consists of a computer module (CPU) and a compatible console module (CON). Computers can be controlled in near real-time – both in extender and matrix applications. The VisionXS-DP-UHR series supports DisplayPort1.2 for ultra-high-resolution video up to  $4096 \times 2160$  (60 Hz) or  $5120 \times 2160$  (50 Hz). Video data is processed pixel-perfectly and offers excellent hand-eye coordination, thanks to bluedec™ – G&D's advanced, multi-stage, lossless compression technology.

## Scope of delivery

| Quantity | Description                    | Article number |
|----------|--------------------------------|----------------|
| 1        | PowerCable-2 Standard cable 2m | A6300057       |
| 1        | DP1.4-Cable-M/M-2 SK13357 2m   | A6300173       |
| 1        | USB-AM/BM-2 cable USB 2m       | A6300113       |

## Details

### Video

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- EDID data utilization from the workplace monitor
- Flexible EDID profile options for optimized monitor settings

- Resolution up to  
5120 × 2160 @ 50 Hz,  
5120 × 1440 @ 60 Hz,  
4096 × 2160 @ 60 Hz,  
2560 × 1440 @ 144 Hz,  
1920 × 1080 @ 240 Hz

## Signals

- Embedded stereo audio (DisplayPort Digital, 2 channel LPCM, AC3, DTS, sampling rate up to 192 kHz)
- GenericUSB support for USB classes HID (Human Interface Device), SmartCard and mass storage
- The product allows the use of a GenericUSB device via a console module. For this, both the used console module and the used computer module must support the use of a GenericUSB device.
- Embedded USB 2.0 with Full Speed, transparent, all USB classes

## Transmission

- The transmission distance is up to 5,000 meters over fiber singlemode optics, incl. transmission module(s)/SFP transceiver(s)

## Device

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- Compact design for space-saving installation within a VisionXS DeviceCarrier (1 or 3 RU)
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)
- PowerPack not included in the scope of delivery
- DT variant: Optional redundant power supply via an internal power unit for high reliability
- Fanless variant: fanless model

## Warranty

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

# Features

## Security features

- Bootloader, operating system, and firmware form a "Trusted Computing Platform" with automatic integrity checks during system startup
- Integrated Trusted Platform Module (TPM) protects all access and configuration data from being spied on or tampered with by third parties
- Console modules do not store security-relevant information such as login credentials, which could be extracted in the event of device loss
- Early detection of security incidents or unusual activities through continuous monitoring via Syslog, monitoring, and SNMP
- Comprehensive rights management and user administration, allowing precise control over which user can access which resources
- Option for activatable access protection (default operating mode in matrix systems), in which authentication is required before accessing computer sources
- Support for external directory services (Active Directory, Radius, LDAP) to meet company security policies
- To comply with individual password policies and improve security, password complexity can be configured system-wide
- Configurable login options, such as displaying terms of use or setting the maximum acceptable number of failed login attempts, can enhance system security
- Auto Backup Function: Automates backups at user-defined intervals and replaces manual intervention – ensuring reliable, timely data protection without the need for continuous monitoring
- Freeze function: If the video signal is lost, the last displayed image is frozen and highlighted with a colored frame and timer
- 2-Factor-Authentication (2FA) – is integrated by default in KVM extenders and enhances security by requiring a second, possession-based factor during user authentication:
  - The traditional password authentication is combined with a time-limited, single-use code (Time-Based-One-Time-Password - TOTP)
  - You can choose between using the internal authentication server provided in the device or an external directory service
  - Authenticator apps or hardware token can be used
  - This additional layer of protection prevents unauthorized access and ensures the highest level of security, particularly in sensitive IT environments

## Operation features

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system

- Compatibility with special USB-HID input devices
- Operation via multilingual on-screen display (OSD) and hotkeys
- Configuration and update via the multilingual HTML5 web interface “Config Panel 21” (Java-free)
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness

## Extensions

### Device


- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply
- Device mounting via G&D 19” DeviceCarrier for VisionXS (1 or 3 RU)

### System extension

- Transm. Redundancy Option (comparable to UC/CON-2): Devices are prepared for transmission redundancy without additional hardware and can be activated via software feature key.
  - Computer modules can connect to various counterparts, such as compatible console modules or KVM matrix switches
  - Console modules can connect to different counterparts, such as compatible computer modules or KVM matrix switches, with switching controlled via hotkey or automatically depending on configuration
  - U2 variants do not support the Transm. Redundancy Option as the 2nd transmission interface is used for the transmission of USB 2.0 data
- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.

## Panels and connectors

### Front



| Aperture designation | Design             | Description                    |
|----------------------|--------------------|--------------------------------|
| USB CPU              | USB-B socket 2.0   | Connection to computer - USB   |
| DP CPU               | DisplayPort socket | Connection to computer - Video |

## Back

| Aperture designation | Design            | Description                                                            |
|----------------------|-------------------|------------------------------------------------------------------------|
| Transmission 1       | LC-Duplex socket  | Data transmission to console module or matrix switch (FIBER)           |
| Transmission 2       | LC-Duplex socket  | Data transmission to console module or matrix switch redundant (FIBER) |
| Service              | Micro-USB socket  | Port for service purposes                                              |
| Network              | RJ45 socket       | Port for IP network                                                    |
| Main Power           | Mini-DIN 4 socket | Power supply DC                                                        |
| Red. Power           | IEC plug 320 C14  | Power supply AC redundant                                              |

## Technical data

|                     |                                 |                                     |
|---------------------|---------------------------------|-------------------------------------|
| <b>General</b>      | Product group                   | KVM extenders                       |
|                     | Product Family                  | VisionXS                            |
|                     | KVM matrix system component     | Computer module (digital)           |
|                     | Power Supply                    | Redundancy without load balancing   |
|                     | Number of transmission channels | 1                                   |
| <b>Transmission</b> | Redundant transmission channels | optional redundant KVM transmission |
|                     | Range                           | 5,000 m (9/125µm, OS1)              |
|                     | Laser class                     | Class 1                             |
|                     | Type of interface               | LC-Duplex                           |
|                     | Wavelength                      | 1,310 nm                            |
|                     | Medium                          | Fiber SM                            |
|                     | Data rate                       | 2.5 Gbit/s                          |
| <b>Video input</b>  | Quantity                        | 1                                   |

|              |                                |                                                                                                                                                                                                                                      |
|--------------|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|              | Format                         | DisplayPort 1.2 (LBR, HBR, HBR2, SingleStream-Transport (SST))                                                                                                                                                                       |
|              | Colour depth                   | 24 bit                                                                                                                                                                                                                               |
|              | Pixel encoding                 | RGB 4:4:4 (24 bpp / 8 bpc)                                                                                                                                                                                                           |
|              | Pixel rate ca.                 | 25 MPixel/s to 600 MPixel/s                                                                                                                                                                                                          |
|              | Vertical frequency             | 24 Hz to 240 Hz                                                                                                                                                                                                                      |
|              | Horizontal frequency           | 25 kHz to 295 kHz                                                                                                                                                                                                                    |
|              | Exemplary resolutions          | 4096 × 2160 (60 Hz)<br>3840 × 2160 (60 Hz)<br>2560 × 1600 (60 Hz)<br>2560 × 1440 (144 Hz)<br>2048 × 2048 (60 Hz)<br>1920 × 1200 (60 Hz)<br>1920 × 1080 (240 Hz)<br>1920 × 1080 (60 Hz)<br>5120 × 1440 (60 Hz)<br>5120 × 2160 (50 Hz) |
|              | General Notes                  | Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.                                                                                                                          |
|              | Supported industry standards   | Display Data Channel Command Interface (DDC/CI)<br>Extended Display Identification Data (EDID)                                                                                                                                       |
|              | Transmission type              | 2-channel LPCM<br>Stereo<br>DTS<br>AC3                                                                                                                                                                                               |
| <b>Audio</b> | Resolutions                    | 24 bit<br>20 bit<br>16 bit                                                                                                                                                                                                           |
|              | Sampling rate                  | up to 192 kHz                                                                                                                                                                                                                        |
|              | Audio support                  | Digital Embedded                                                                                                                                                                                                                     |
|              | Separate USB transmission port | no                                                                                                                                                                                                                                   |
|              | Specification                  | USB 2.0                                                                                                                                                                                                                              |
| <b>USB 1</b> | GenericUSB support             | 1 device                                                                                                                                                                                                                             |
|              | Medium                         | Embedded                                                                                                                                                                                                                             |
|              | Transmission rate              | max. 25 Mbit/s (Full Speed)                                                                                                                                                                                                          |
|              | USB classes                    | Mass Storage (MSC / UMS)<br>Human Interface Device (HID)<br>SmartCard                                                                                                                                                                |
|              | Separate USB transmission port | no                                                                                                                                                                                                                                   |
| <b>USB 2</b> | Specification                  | USB 2.0                                                                                                                                                                                                                              |
|              | Medium                         | Embedded                                                                                                                                                                                                                             |
|              | Transmission rate              | max. 16 Mbit/s (app. Full Speed)                                                                                                                                                                                                     |
|              | Range                          | max. 5,000 m                                                                                                                                                                                                                         |
|              | USB classes                    | All                                                                                                                                                                                                                                  |

|                                 |                                               |                                                                                                                                                                                                                                                                   |
|---------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                 | Quantity                                      | 1                                                                                                                                                                                                                                                                 |
| <b>Network</b>                  |                                               | CAT5                                                                                                                                                                                                                                                              |
|                                 | Medium                                        | CAT6                                                                                                                                                                                                                                                              |
|                                 |                                               | CAT7                                                                                                                                                                                                                                                              |
|                                 | Data rate                                     | 10 Mbit/s                                                                                                                                                                                                                                                         |
|                                 |                                               | 100 Mbit/s                                                                                                                                                                                                                                                        |
| <b>Maintenance</b>              | Update via                                    | ConfigPanel (Network)                                                                                                                                                                                                                                             |
|                                 | Serviceport settings                          | 115200bps (8/N/1)                                                                                                                                                                                                                                                 |
|                                 | Material                                      | anodised aluminium                                                                                                                                                                                                                                                |
| <b>Housing</b>                  | Width ca.                                     | 170 mm                                                                                                                                                                                                                                                            |
|                                 | Height ca.                                    | 40 mm                                                                                                                                                                                                                                                             |
|                                 | Depth ca.                                     | 184 mm                                                                                                                                                                                                                                                            |
|                                 | IP protection class                           | IP20                                                                                                                                                                                                                                                              |
|                                 | Operating temperature                         | 5 °C to 45 °C                                                                                                                                                                                                                                                     |
|                                 | Operating air humidity,<br>non-condensing     | 20 % to 80 %                                                                                                                                                                                                                                                      |
|                                 | Area of application                           | Indoor use                                                                                                                                                                                                                                                        |
|                                 | Maximum operating<br>altitude above sea level | 3,048 m                                                                                                                                                                                                                                                           |
|                                 | Storage temperature                           | -20 °C to 60 °C                                                                                                                                                                                                                                                   |
| <b>Operating<br/>conditions</b> | Storage air humidity,<br>non-condensing       | 15 % to 85 %                                                                                                                                                                                                                                                      |
|                                 | MTBF                                          | 200,000 h at 25°C                                                                                                                                                                                                                                                 |
|                                 | Conformities                                  | FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads)<br>CE compliant (see downloads)<br>UKCA compliant (see downloads) |
|                                 | Quantity                                      | 1                                                                                                                                                                                                                                                                 |
|                                 | Type                                          | External                                                                                                                                                                                                                                                          |
|                                 | Input voltage                                 | 12 VDC                                                                                                                                                                                                                                                            |
| <b>Power supply<br/>1</b>       | Current consumption                           | 1.5 A                                                                                                                                                                                                                                                             |
|                                 | Power consumption idle                        | 12.8 W                                                                                                                                                                                                                                                            |
|                                 | Power consumption max.                        | 16.2 W                                                                                                                                                                                                                                                            |
|                                 | Heat output idle                              | 12.8 W                                                                                                                                                                                                                                                            |
|                                 | Heat output max.                              | 16.2 W                                                                                                                                                                                                                                                            |
|                                 | Quantity                                      | 1                                                                                                                                                                                                                                                                 |
|                                 | Type                                          | Internal                                                                                                                                                                                                                                                          |
| <b>Power supply<br/>2</b>       | Input voltage                                 | 100-240 VAC                                                                                                                                                                                                                                                       |
|                                 | Input frequency                               | 60-50 Hz                                                                                                                                                                                                                                                          |
|                                 | Current consumption                           | 0.5-0.3 A                                                                                                                                                                                                                                                         |
|                                 | Power consumption idle                        | 14.6-14.2 W                                                                                                                                                                                                                                                       |



|                        |             |
|------------------------|-------------|
| Power consumption max. | 18.3-17.9 W |
| Heat output idle       | 14.6-14.2 W |
| Heat output max.       | 18.3-17.9 W |

## more variants

| Description                                                                                                       | Article number |
|-------------------------------------------------------------------------------------------------------------------|----------------|
| <b>VisionXS-CPU-F(S)-DP-UHR</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode          | A1110320       |
| <b>VisionXS-CPU-F(S)-DP-UHR-A</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode        | A1110321       |
| <b>VisionXS-CPU-F(S)-DP-UHR-A-U</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode      | A1110322       |
| <b>VisionXS-CPU-F(S)-DP-UHR-A-U2</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode     | A1110618       |
| <b>VisionXS-CPU-F(S)-DP-UHR-AR-DT</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode    | A1110324       |
| <b>VisionXS-CPU-F(S)-DP-UHR-AR-U-DT</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode  | A1110325       |
| <b>VisionXS-CPU-F(S)-DP-UHR-AR-U2-DT</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode | A1110617       |
| <b>VisionXS-CPU-F(S)-DP-UHR-DT</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode       | A1110326       |
| <b>VisionXS-CPU-F(S)-DP-UHR-U</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode        | A1110323       |
| <b>VisionXS-CPU-F(S)-DP-UHR-U2</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode       | A1110619       |
| <b>VisionXS-CPU-F(S)-DP-UHR-U2-DT</b><br>Computer module to extend DisplayPort1.2 signals via fiber singlemode    | A1110620       |

## Contact

### We are here for you!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### Technical sales

Tel.: +1-833-928-1976  
 Fax: +1-833-928-1976  
 E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### Headquarters

Guntermann & Drunck GmbH Systementwicklung  
 Obere Leimbach 9 | 57074 Siegen | NRW | Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

## **US Office**

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

## **Middle east office**

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

## **APAC OFFICE**

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)