

# CCD-FAN-OUT-CARD-80-C CARD F. CCD-80-C

KVM matrix systems, Article number A2300082



The modular fan module for the ControlCenter-Digital can be hot-plugged or hot-swapped.

## DETAILS

### DEVICE

- Placed at the sides of the ControlCenter-Digital
- Modular design
- Can be easily replaced or cleaned during operation
- incompatible with hardware 2.0

### WARRANTY

- A 3-year, free of charge product guarantee

## TECHNICAL DATA

|                      |                                            |                                |
|----------------------|--------------------------------------------|--------------------------------|
| General              | Brand                                      | G&D                            |
|                      | Product group                              | KVM matrix switches            |
|                      | Product Family                             | ControlCenter-Digital          |
|                      | Country of origin                          | Germany                        |
|                      | KVM matrix system component                | Central module comp. (digital) |
| Maintenance          | Update via                                 | ConfigPanel (Network)          |
|                      | Serviceport settings                       | 115200bps (8/N/1)              |
| Housing              | Material                                   | Anodised aluminium             |
|                      | Active cooling (fan)                       | yes                            |
|                      | IP protection class                        | IP20                           |
|                      | Weight ca.                                 | 0.35 kg                        |
| Operating conditions | Operating environment temperature          | 5 °C to 45 °C                  |
|                      | Operating air humidity, non-condensing     | 20 % to 80 %                   |
|                      | Area of application                        | Indoor use                     |
|                      | Maximum operating altitude above sea level | 3,048 m                        |
|                      | Storage environment temperature            | -20 °C to 55 °C                |
|                      | Storage air humidity, non-condensing       | 15 % to 85 %                   |
|                      | MTBF                                       | 60,000 h at 25°C               |

## Conformities

CE compliant (see downloads)  
UKCA compliant (see downloads)  
FCC compliant (see manual)  
TAA compliant (see downloads)  
EAC compliant (see downloads)  
RoHS compliant (see downloads)  
WEEE (reg. no. DE30763240)  
REACH compliant (see downloads)

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +49 271 23872-333  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH  
Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)