CCD-IO16-CARD-FIBER BLANK WITHOUT SFP-TRANSC.

KVM matrix systems, Article number A2300086



I/O cards are modular cards for the ControlCenter-Digital with multiple in-/output ports to which you can connect user or computer modules.

DETAILS

DEVICE

- Establishes the connection between the ControlCenter-Digital and its computer modules and user modules
- 16 ports, which automatically detect the type of module connected to the matrix switch

WARRANTY

- A 3-year, free of charge product guarantee

EXTENSIONS

DEVICE

- matching SFP transceivers are separately available

TECHNICAL DATA

General	Brand	G&D
	Product group	KVM matrix switches
	Product Family	ControlCenter-Digital
	Country of origin	Germany
	KVM matrix system component	Central module comp. (digital)
Transmission	Number of transmission channels	16
	Redundant transmission channels	no redundant KVM transmission
	Range	5,000 m (9/125µm, OS1) 100 m (62.5/125µm) 200 m (50.0/125µm, OM2) 400 m (50.0/125µm, OM3)
	Laser class	Class 1
	Type of interface	LC-Duplex
	Wavelength	1,310 nm 850 nm
	Medium	Fiber SM Fiber MM
	Data rate	2.5 Gbit/s
Maintenance	Update via	ConfigPanel (Network)
	Serviceport settings	115200bps (8/N/1)
Housing	Material	Anodised aluminium
	Active cooling (fan)	yes

	IP protection class	IP20
	Weight ca.	0.51 kg / 1.12 lb
Operating conditions	Operating environment temperature	5 °C to 45 °C / 41 °F to 113 °F
	Operating air humidity, non-condensing	20 % to 80 %
	Area of application	Indoor use
	Maximum operating altitude above sea level	3,048 m
	Storage environment temperature	-20 °C to 55 °C / -4 °F to 131 °F
	Storage air humidity, non-condensing	15 % to 85 %
	MTBF	100,000 h at 25°C (77 °F)
	Conformities	CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)

MORE VARIANTS

Description	Article number
CCD-IO16-Card-CAT card f. CCD 16xCAT Input/output module of the ControlCenter-Digital system	A2300061
CCD-IO16-Card-Fiber(M) card f. CCD 16xFiber(M) Input/output module of the ControlCenter-Digital system	A2300062
CCD-IO16-Card-Fiber(S) card f. CCD 16xFiber(S) Input/output module of the ControlCenter-Digital system	A2300063
CCD-IO16-Card-Multi card f. CCD 16xMulti Input/output module of the ControlCenter-Digital system	A2300085
CCD-IO16-Card-Trunk4 blank without SFP-Transc. Input/output module of the ControlCenter-Digital system including 4x 10G interfaces - without SFP-Transceiver	A2300098
CCD-IO16-Card-Trunk4(M) Input/output module of the ControlCenter-Digital system including 4x 10G interfaces	A2300096
CCD-IO16-Card-Trunk4(S) Input/output module of the ControlCenter-Digital system including 4x 10G interfaces	A2300097

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +1-833-928-1976
Fax: +1-833-928-1976
E-Mail: sales.us@gdsys.com

HEADQUARTERS

Panoptec Europe GmbH
Obere Leimbach 9 | 57074 Siegen | NRW | Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@panoptec.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Panoptec Europe GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales@panoptec.com

APAC OFFICE

Panoptec Europe GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales@panoptec.com