# CCD-IO16-CARD-MULTI CARD F. CCD 16XMULTI

KVM matrix systems, Article number A2300085



I/O cards are modular cards for the ControlCenter-Digital with multiple in-/output ports to which you can connect user or computer modules.

# DETAILS

## DEVICE

- Lets you connect third-party devices to the matrix from where they can be switched, too
- Supported signals:
  - SDI
  - HD-SDI
  - 3G-SDI
  - USB 3.0 Spectra
  - 1Gb ethernet

## WARRANTY

- A 3-year, free of charge product guarantee

# TECHNICAL DATA

| | | |
|---|---|---|
| General | Brand | G&D |
| | Product group | KVM matrix switches |
| | Product Family | ControlCenter-Digital |
| | Country of origin | Germany |
| | KVM matrix system component | Central module comp. (digital) |
| Maintenance | Update via | ConfigPanel (Network) |
| | Serviceport settings | 115200bps (8/N/1) |
| Housing | Material | Anodised aluminium |
| | Active cooling (fan) | yes |
| | IP protection class | IP20 |
| | Weight ca. | 0.46 kg / 1.01 lb |
| Operating conditions | Operating environment temperature | 5 °C to 45 °C / 41 °F to 113 °F |
| | Operating air humidity, non-condensing | 20 % to 80 % |
| | Area of application | Indoor use |
| | Maximum operating altitude above sea level | 3,048 m |
| | Storage environment temperature | -20 °C to 55 °C / -4 °F to 131 °F |
| | Storage air humidity, non-condensing | 15 % to 85 % |
| | MTBF | 100,000 h at 25°C (77 °F) |

| | | |
|---|---|---|
| | Conformities | CE compliant (see downloads)<br>UKCA compliant (see downloads)<br>FCC compliant (see manual)<br>TAA compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads) |

## MORE VARIANTS

| Description | Article number |
|---|---|
| **CCD-IO16-Card-CAT card f. CCD 16xCAT**<br>Input/output module of the ControlCenter-Digital system | A2300061 |
| **CCD-IO16-Card-Fiber blank without SFP-Transc.**<br>Input/output module of the ControlCenter-Digital system | A2300086 |
| **CCD-IO16-Card-Fiber(M) card f. CCD 16xFiber(M)**<br>Input/output module of the ControlCenter-Digital system | A2300062 |
| **CCD-IO16-Card-Fiber(S) card f. CCD 16xFiber(S)**<br>Input/output module of the ControlCenter-Digital system | A2300063 |
| **CCD-IO16-Card-Trunk4 blank without SFP-Transc.**<br>Input/output module of the ControlCenter-Digital system including 4x 10G interfaces - without SFP-Transceiver | A2300098 |
| **CCD-IO16-Card-Trunk4(M)**<br>Input/output module of the ControlCenter-Digital system including 4x 10G interfaces | A2300096 |
| **CCD-IO16-Card-Trunk4(S)**<br>Input/output module of the ControlCenter-Digital system including 4x 10G interfaces | A2300097 |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +1-833-928-1976
Fax: +1-833-928-1976
E-Mail: sales.us@gdsys.com

### HEADQUARTERS

Panoptec Europe GmbH
Obere Leimbach 9 | 57074 Siegen | NRW | Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@panoptec.com

### US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

### MIDDLE EAST OFFICE

Panoptec Europe GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales@panoptec.com

### APAC OFFICE

Panoptec Europe GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales@panoptec.com