

CCD-SWITCH-CARD-160 2.0 CARD F. CCD-160

KVM matrix systems, Article number A2300138



The modular switch card is the central unit containing the switching logic of the ControlCenter-Digital.

DETAILS

DEVICE

- Provides the matrix's central switching logic
- Hot-swappable and can be easily replaced
- incompatible with hardware 1.0

WARRANTY

- A 3-year, free of charge product guarantee

TECHNICAL DATA

General	Brand	G&D
	Product group	KVM matrix switches
	Product Family	ControlCenter-Digital
	Country of origin	Germany
	KVM matrix system component	Central module comp. (digital)
Maintenance	Update via	ConfigPanel (Network)
	Serviceport settings	115200bps (8/N/1)
Housing	Material	Anodised aluminium
	Active cooling (fan)	yes
	IP protection class	IP20
Operating conditions	Operating environment temperature	5 °C to 45 °C
	Operating air humidity, non-condensing	20 % to 80 %
	Area of application	Indoor use
	Maximum operating altitude above sea level	3,048 m
	Storage environment temperature	-20 °C to 55 °C
	Storage air humidity, non-condensing	15 % to 85 %
	MTBF	100,000 h at 25°C

Conformities

CE compliant (see downloads)
UKCA compliant (see downloads)
FCC compliant (see manual)
TAA compliant (see downloads)
EAC compliant (see downloads)
RoHS compliant (see downloads)
WEEE (reg. no. DE30763240)
REACH compliant (see downloads)

MORE VARIANTS

Description	Article number
CCD-Switch-Card-160 card f. CCD-160 Module for the central processing unit of the ControlCenter-Digital-160	A2300059
CCD-Switch-Card-288 card f. CCD-288 Module for the central processing unit of the ControlCenter-Digital-288	A2300058
CCD-Switch-Card-80 card f. CCD-80 Module for the central processing unit of the ControlCenter-Digital-80	A2300060

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +49 271 23872-333
Fax: +49 271 23872-120
E-Mail: sales@panoptec.com

HEADQUARTERS

Panoptec Europe GmbH
Obere Leimbach 9 | 57074 Siegen | NRW |
Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@panoptec.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Panoptec Europe GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales@panoptec.com

APAC OFFICE

Panoptec Europe GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales@panoptec.com