

# CCD-SWITCH-CARD-160 CARD F. CCD-160

KVM matrix systems, Article number A2300059



The modular switch card is the central unit containing the switching logic of the ControlCenter-Digital.



## DETAILS

### DEVICE

- Provides the matrix's central switching logic
- Hot-swappable and can be easily replaced
- incompatible with hardware 2.0

### WARRANTY

- A 3-year, free of charge product guarantee

## TECHNICAL DATA

General	Brand	G&D
	Product group	KVM matrix switches
	Product Family	ControlCenter-Digital
	Country of origin	Germany
	KVM matrix system component	Central module (digital)
Maintenance	Update via	ConfigPanel (Network)
	Serviceport settings	115200bps (8/N/1)
Housing	Material	Anodised aluminium
	Active cooling (fan)	yes
	IP protection class	IP20
	Weight ca.	1.47 kg
Operating conditions	Operating environment temperature	5 °C to 45 °C
	Operating air humidity, non-condensing	20 % to 80 %
	Area of application	Indoor use
	Maximum operating altitude above sea level	3,048 m
	Storage environment temperature	-20 °C to 55 °C
	Storage air humidity, non-condensing	15 % to 85 %
	MTBF	100,000 h at 25°C



Conformities

- CE compliant (see downloads)
- UKCA compliant (see downloads)
- FCC compliant (see manual)
- TAA compliant (see downloads)
- EAC compliant (see downloads)
- RoHS compliant (see downloads)
- WEEE (reg. no. DE30763240)
- REACH compliant (see downloads)

## MORE VARIANTS

Description	Article number
<b>CCD-Switch-Card-160 2.0 card f. CCD-160</b> Module for the central processing unit of the ControlCenter-Digital-160 2.0	A2300138
<b>CCD-Switch-Card-288 card f. CCD-288</b> Module for the central processing unit of the ControlCenter-Digital-288	A2300058
<b>CCD-Switch-Card-80 card f. CCD-80</b> Module for the central processing unit of the ControlCenter-Digital-80	A2300060

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +1-833-928-1976  
Fax: +1-833-928-1976  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)