

# CCD-SWITCH-CARD-288 CARD F. CCD-288

KVM matrix systems, Article number A2300058



The modular switch card is the central unit containing the switching logic of the ControlCenter-Digital.



## DETAILS

### DEVICE

- Provides the matrix's central switching logic
- Hot-swappable and can be easily replaced
- incompatible with hardware 2.0

### WARRANTY

- A 3-year, free of charge product guarantee

## TECHNICAL DATA

|                      |                                            |                          |
|----------------------|--------------------------------------------|--------------------------|
| General              | Product group                              | KVM matrix switches      |
|                      | Product Family                             | ControlCenter-Digital    |
|                      | KVM matrix system component                | Central module (digital) |
| Maintenance          | Update via                                 | ConfigPanel (Network)    |
|                      | Serviceport settings                       | 115200bps (8/N/1)        |
| Housing              | Material                                   | anodised aluminium       |
|                      | IP protection class                        | IP20                     |
|                      | Weight ca.                                 | 1.58 kg                  |
| Operating conditions | Operating temperature                      | 5 °C to 45 °C            |
|                      | Operating air humidity, non-condensing     | 20 % to 80 %             |
|                      | Area of application                        | Indoor use               |
|                      | Maximum operating altitude above sea level | 3,048 m                  |
|                      | Storage temperature                        | -20 °C to 55 °C          |
|                      | Storage air humidity, non-condensing       | 15 % to 85 %             |
|                      | MTBF                                       | 100,000 h at 25°C        |



|  |              |                                                                                                                                                                                                                                                                   |
|--|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Conformities | CE compliant (see downloads)<br>UKCA compliant (see downloads)<br>FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads) |
|--|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## MORE VARIANTS

| Description                                                                                                                   | Article number |
|-------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>CCD-Switch-Card-160 2.0 card f. CCD-160</b><br>Module for the central processing unit of the ControlCenter-Digital-160 2.0 | A2300138       |
| <b>CCD-Switch-Card-160 card f. CCD-160</b><br>Module for the central processing unit of the ControlCenter-Digital-160         | A2300059       |
| <b>CCD-Switch-Card-80 card f. CCD-80</b><br>Module for the central processing unit of the ControlCenter-Digital-80            | A2300060       |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +1-833-928-1976  
Fax: +1-833-928-1976  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)