

CCD-SWITCH-CARD-80 CARD F. CCD-80

KVM matrix systems, Article number A2300060



The modular switch card is the central unit containing the switching logic of the ControlCenter-Digital.

DETAILS

DEVICE

- Provides the matrix's central switching logic
- Hot-swappable and can be easily replaced
- incompatible with hardware 2.0

WARRANTY

- A 3-year, free of charge product guarantee

TECHNICAL DATA

| | | |
|----------------------|--|--------------------------|
| General | Product group | KVM matrix switches |
| | Product Family | ControlCenter-Digital |
| | KVM matrix system component | Central module (digital) |
| Maintenance | Update via | ConfigPanel (Network) |
| | Serviceport settings | 115200bps (8/N/1) |
| Housing | Material | Anodised aluminium |
| | IP protection class | IP20 |
| | Weight ca. | 0.77 kg |
| Operating conditions | Operating environment temperature | 5 °C to 45 °C |
| | Operating air humidity, non-condensing | 20 % to 80 % |
| | Area of application | Indoor use |
| | Maximum operating altitude above sea level | 3,048 m |
| | Storage environment temperature | -20 °C to 55 °C |
| | Storage air humidity, non-condensing | 15 % to 85 % |
| | MTBF | 100,000 h at 25°C |

| | | |
|--|---------------------|---|
| | <p>Conformities</p> | <p>CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)</p> |
|--|---------------------|---|

MORE VARIANTS

| Description | Article number |
|---|----------------|
| CCD-Switch-Card-160 2.0 card f. CCD-160 Module for the central processing unit of the ControlCenter-Digital-160 2.0 | A2300138 |
| CCD-Switch-Card-160 card f. CCD-160 Module for the central processing unit of the ControlCenter-Digital-160 | A2300059 |
| CCD-Switch-Card-288 card f. CCD-288 Module for the central processing unit of the ControlCenter-Digital-288 | A2300058 |

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +49 271 23872-333
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung
Obere Leimbach 9 | 57074 Siegen | NRW |
Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Guntermann & Drunck GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales.me@gdsys.com

APAC OFFICE

Guntermann & Drunck GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales.apac@gdsys.com