

# DL-DVI-MUX4-NT-MC4

KVM switches, Article number A2100200



Front



Back

The KVM switch DL-DVI-MUX4-NT lets you operate up to four computers with Dual-link DVI via one workplace. Switching between computers is done either via the push buttons on the front panel, configurable key combinations, the integrated EasyControl tool, XML remote control via API and SNMP, or an additional serial device via the RS232 interface. You can use various Monitoring & SNMP features via the network interfaces. These can also be used to configure the device via the Config Panel.

## SCOPE OF DELIVERY

Quantity	Description	Article number
2	PowerCable-2 Standard cable 2m	A6300057
1	19" RM-Set-436-3RU	A7000015
1	Safety instructions flyer - FCC class B	A9100371

## DETAILS

### VIDEO

- EDID data utilization from the workplace monitor
- Resolution (input and output side) up to  
2560 × 1600 @ 60 Hz,  
1920 × 1440 @ 75 Hz
- Resolution (input and output side) up to  
2560 × 1600 @ 60 Hz,  
1920 × 1440 @ 75 Hz

### SIGNALS

- Transparent audio signals (stereo, analog)
- USB 3.1 gen1 with SuperSpeed, all USB classes

### DEVICE

- Access to standard interfaces of the computer, with no software installation required
- MultiChannel variants (MC): Modules for multi-monitor workplaces with multi-channel video

### WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

## FEATURES

### SECURITY FEATURES

- Early detection of security incidents or unusual activities through continuous monitoring via Syslog, monitoring, and SNMP
- Redundant network interface
- Redundant internal power packs
- Auto Backup Function: Automates backups at user-defined intervals and replaces manual intervention – ensuring reliable, timely data protection without the need for continuous monitoring
- 2-Factor-Authentication (2FA) – is integrated by default in MUX-NT series and enhances security by requiring a second, possession-based factor during user authentication:
  - The traditional password authentication is combined with a time-limited, single-use code (Time-Based-One-Time-Password - TOTP)
  - You can choose between using the internal authentication server provided in the device or an external directory service
  - Authenticator apps or hardware token can be used
  - This additional layer of protection prevents unauthorized access and ensures the highest level of security, particularly in sensitive IT environments

### OPERATION FEATURES

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Configuration and update via the multilingual HTML5 web interface “Config Panel 21” (Java-free)

## EXTENSIONS

### CONTROL OPTIONS

- With the OperatorPanel, you can switch your KVM switch comfortably from your desk by pressing a button. Now you can install the switch anywhere to save space.

## TECHNICAL DATA

General	Brand	G&D
	Product group	KVM switches
	Product Family	MUX-NT
	Country of origin	Germany
	Number of workstations	1
	Number of sources	4
	Power Supply	Redundancy without load balancing
Video input 1	Quantity	2
	Format	DualLink DVI
	Colour depth	24 bit
	Pixel encoding	RGB 4:4:4 (24 bpp / 8 bpc)
	Pixel rate ca.	25 MPixel/s to 330 MPixel/s
	Vertical frequency	20 Hz to 120 Hz
	Horizontal frequency	25 kHz to 135 kHz
	Exemplary resolutions	3840 × 2160 (30 Hz) 2560 × 1600 (60 Hz) 2048 × 2160 (60 Hz) 2048 × 2048 (60 Hz)
	General Notes	Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.
	Supported industry standards	Enhanced Display Data Channel (E-DDC)

Video input 2	Quantity	2
	Format	VGA
	Colour depth	24 bit
	Pixel rate ca.	0 MHz to 400 MHz
	Vertical frequency	20 Hz to 120 Hz
	Horizontal frequency	25 kHz to 135 kHz
	Exemplary resolutions	1920 × 1440 (75 Hz)
	General Notes	Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.
	Supported industry standards	Enhanced Display Data Channel (E-DDC)
Video output 1	Quantity	2
	Format	DualLink DVI
	Colour depth	24 bit
	Pixel rate ca.	25 MPixel/s to 330 MPixel/s
	Vertical frequency	20 Hz to 120 Hz
	Horizontal frequency	25 kHz to 135 kHz
	Exemplary resolutions	3840 × 2160 (30 Hz) 2560 × 1600 (60 Hz) 2048 × 2160 (60 Hz) 2048 × 2048 (60 Hz)
	General Notes	Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.



	Supported industry standards	Enhanced Display Data Channel (E-DDC)
Video output 2	Quantity	2
	Format	VGA
	Colour depth	24 bit
	Pixel rate ca.	0 MHz to 400 MHz
	Vertical frequency	20 Hz to 120 Hz
	Horizontal frequency	25 kHz to 135 kHz
	Exemplary resolutions	1920 x 1440 (75 Hz)
	General Notes	Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.
	Supported industry standards	Enhanced Display Data Channel (E-DDC)
Audio	Transmission type	Stereo Transparent
	Resolutions	24 bit digital
	Sampling rate	up to 96 kHz
	Bandwidth	22 kHz
	Audio support	Analog
USB	Separate USB transmission port	no
	Specification	USB 3.1 Gen 1
	Transmission rate	max. 5,000 Mbit/s (SuperSpeed)

	Power (output)	900 mA (HighPower)
	USB classes	All
Network	Quantity	2
	Medium	CAT7 CAT6 CAT5
	Data rate	100 Mbit/s 10 Mbit/s
Maintenance	Update via	ConfigPanel (Network)
	Serviceport settings	115200bps (8/N/1)
Housing	Material	Anodised aluminium
	Active cooling (fan)	no
	Width ca.	436 mm
	Height ca.	132 mm
	Depth ca.	210 mm
	IP protection class	IP20
	Weight ca.	3.76 kg
Operating conditions	Operating environment temperature	5 °C to 45 °C
	Operating air humidity, non-condensing	20 % to 80 %
	Area of application	Indoor use
	Maximum operating altitude above sea level	3,048 m

	Storage environment temperature	-20 °C to 55 °C
	Storage air humidity, non-condensing	15 % to 85 %
	MTBF	200,000 h at 25°C
	Conformities	CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)
Power supply	Quantity	2
	Type	Internal
	Input voltage	100-240 VAC
	Input frequency	60-50 Hz
	Current consumption	0.6-0.4 A
	Power consumption idle	13.6-14.2 W
	Power consumption max.	28.4-28.1 W
	Heat output idle	28.1 W
	Heat output max.	16.1 W

## ACCESSORY PRODUCTS

Image	Description	Article number
	<b>USB-Service-2 cable 2m</b> Cable for system updates and configuration	A6200103
	<b>CPU-MC4-DVID-DL-U3-2 cable DVI-D 2m</b> Cable set to connect a computer via its DL-DVI, audio, PS/2, USB 2.0 and USB 3.0 interfaces	A6100181
	<b>CPU-MC4-DVID-DL-U-2 cable DVI-D 2m</b> Computer connection cable for quad DVI-D (dual-link)	A6100128
	<b>PowerCable-3 Standard cable 3m</b> Cable to connect the power supply type Germany	A6300066
	<b>PowerCable-5 Standard cable 5m</b> Cable to connect the power supply type Germany	A6300065
	<b>Audio-M/M-2-ferrite cable 2m</b> Audio connection cable with ferrite core	A6300083
	<b>Audio-M/M-3-ferrite cable 3m</b> Audio connection cable with ferrite core	A6300118
	<b>Audio-M/M-5-ferrite cable 5m</b> Audio connection cable with ferrite core	A6300085
	<b>DVI-D-DL-M/M-2 cable DVI-D 2m</b> Single cable for connecting a digital dual-link video channel	A6300100
	<b>DVI-D-DL-M/M-3 cable DVI-D 3m</b> Single cable for connecting a digital dual-link video channel	A6300164
	<b>DVI-D-DL-M/M-5 cable DVI-D 5m</b> Single cable for connecting a digital dual-link video channel	A6300104
	<b>USB-AM/BM-2 cable USB 2m</b> USB cable, Type-A Plug/Type-B Plug	A6300113
	<b>USB-AM/BM-3 cable USB 3m</b> USB cable, Type-A Plug/Type-B Plug	A6300114
	<b>USB-AM/BM-5 cable USB 5m</b> USB cable, Type-A Plug/Type-B Plug	A6300111
	<b>USB3.0-AM/BM-1 cable USB3.0 1m</b> USB3.0 cable, Type-A Plug/Type-B Plug	A6300144

Image	Description	Article number
	<b>USB3.0-AM/BM-2 cable USB3.0 2m</b> USB3.0 cable, Type-A Plug/Type-B Plug	A6300145
	<b>USB3.0-AM/BM-3 cable USB3.0 3m</b> USB3.0 cable, Type-A Plug/Type-B Plug	A6300146

## MORE VARIANTS

Description	Article number
<b>DL-DVI-MUX4-NT</b> KVM switch to operate up to 4 computers with Dual-Link-DVI interface via one console	A2100197
<b>DL-DVI-MUX4-NT-DCS Dry Contacts Switching</b> KVM switch to operate up to 4 computers with Dual-Link-DVI interface via one console	A2100203
<b>DL-DVI-MUX4-NT-MC2</b> KVM switch to operate up to 4 computers with 2 Dual-Link-DVI interfaces each via one console	A2100198
<b>DL-DVI-MUX4-NT-MC2-R</b> KVM switch to operate up to 4 computers with 2 Dual-Link-DVI interfaces each via one console	A2100205
<b>DL-DVI-MUX4-NT-MC3</b> KVM switch to operate up to 4 computers with 3 Dual-Link-DVI interfaces each via one console	A2100199
<b>DL-DVI-MUX4-NT-R</b> KVM switch to operate up to 4 computers with Dual-Link-DVI interface via one console	A2100204

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +49 271 23872-333  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)