

# REMOTEACCESS-CPU-FIBER(S)-UG BASIC

KVM matrix systems, Article number A2320364



With the RemoteAccess-CPU, you can integrate virtual machines into your KVM matrix installation and benefit from hands-on KVM functions, even in hybrid systems. Since cloud computing and virtualization are becoming increasingly important, we will see more hybrid infrastructures in the future. But how can you link such hybrid structures as flexibly as possible? How do you standardize their use so that operators can handle them easily, efficiently and in line with their needs? The RemoteAccess-CPU provides the answers to these questions.

## SCOPE OF DELIVERY

Quantity	Description	Article number
1	Safety instructions flyer - FCC class B	A9100371

## DETAILS

### VIDEO

- Compressed, pixel perfect, ideal hand-eye coordination
- Resolution up to 2560 × 1600 @ 60 Hz

### SIGNALS

- Embedded stereo audio (Digital, 2 channel LPCM)
- GenericUSB support for USB class HID (Human Interface Device).
- The product allows the simultaneous use of up to four GenericUSB devices via a console module. For this, both the used console module and the used computer module must support the use of up to four GenericUSB devices.

### TRANSMISSION

- Supported network protocols:
  - RDP
  - VNC
  - SSH
  - additional via streaming feature (see extensions)
- The transmission distance is up to 5,000 meters over fiber singlemode optics, incl. transmission module(s)/SFP transceiver(s)

### DEVICE

- PowerPack not included in the scope of delivery for Basic variants

### WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

## FEATURES

### DEVICE

- Thin client functionality exactly tailored to a G&D matrix:  
The device is equipped with a powerful, reliable industrial board and offers a platform with integrated thin client functionality. Therefore, you don't need a separate thin client.

### OPERATION FEATURES

- Configuration and update via the multilingual HTML5 web interface "Config Panel 21" (Java-free)
- Integration of any number of virtual sources into the KVM matrix including automatised logins (single sign on via matrix OSD)
- Operation (switching between channels, push-get, etc.) via on-screen display
- Selection of virtual and physical sources within the matrix environment via on-screen display's select menu (target list)
- Multi user access: Via G&D's KVM system, multiple operators can use the same RemoteAccess-CPU to simultaneously connect and operate the same virtual machine.

## EXTENSIONS

### TRANSMISSION

- The streaming feature allows you to access various streaming sources. The following sources can be streamed: H.265 and H.264 video streams, VP8 and VP9 video streams, MP3 audio streams, MP3 audio streams and AC3 audio streams.

### DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply

## TECHNICAL DATA




General	Brand	G&D
	Product group	RemoteAccess
	Product Family	RemoteAccess-CPU
	Country of origin	Germany
	Number of sources	1
	KVM matrix system component	Computer module (digital)
	Power Supply	no redundancy
Transmission	Number of transmission channels	1
	Redundant transmission channels	no redundant KVM transmission
	Range	5,000 m (9/125µm, OS1)
	Laser class	Class 1
	Type of interface	LC-Duplex
	Wavelength	1,310 nm
	Medium	Fiber SM
	Data rate	2.5 Gbit/s
Video output	Quantity	1
	Colour depth	24 bit
	Pixel rate ca.	25 MPixel/s to 330 MPixel/s

	Exemplary resolutions	2560 × 1600 (60 Hz) 2560 × 1440 (60 Hz) 1920 × 1200 (60 Hz) 1920 × 1080 (60 Hz) 1600 × 1200 (60 Hz) 1680 × 1050 (60 Hz) 1280 × 1024 (60 Hz) 1024 × 768 (60 Hz)
Audio	Transmission type	Stereo 2-channel LPCM
	Resolutions	24 bit 20 bit 16 bit
	Sampling rate	up to 48 kHz
	Audio support	Digital Embedded
USB	Separate USB transmission port	no
	Specification	USB 2.0
	GenericUSB support	up to 4 devices
	Medium	Embedded
	Transmission rate	8.5 Mbit/s (Full Speed)
	USB classes	Human Interface Device (HID)
Network	Quantity	1
	Medium	CAT5 CAT6 CAT7
	Data rate	1 Gbit/s 100 Mbit/s 10 Mbit/s

Maintenance	Update via	ConfigPanel (Network)
	Serviceport settings	115200bps (8/N/1)
Housing	Material	Anodised aluminium
	Active cooling (fan)	yes
	Width ca.	105 mm
	Height ca.	26 mm
	Depth ca.	184 mm
	IP protection class	IP20
Operating conditions	Operating environment temperature	5 °C to 45 °C
	Operating air humidity, non-condensing	20 % to 80 %
	Area of application	Indoor use
	Maximum operating altitude above sea level	3,048 m
	Storage environment temperature	-20 °C to 60 °C
	Storage air humidity, non-condensing	15 % to 85 %
	MTBF	280,000 h at 25°C
	Conformities	CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)

Power supply	Quantity	1
	Type	External
	Input voltage	12 VDC
	Current consumption	1.2 A
	Power consumption idle	8.52 W
	Power consumption max.	9.96 W
	Heat output idle	8.52 W / 29.07 BTU/h
	Heat output max.	9.96 W / 33.98 BTU/h

## ACCESSORY PRODUCTS

Image	Description	Article number
	<p><b>USB-Service-2 cable 2m</b> Cable for system updates and configuration</p>	A6200103
	<p><b>PowerPack 12 Type 3 12V/2A</b> 24W power supply with 2m powercable</p>	A4110013
	<p><b>CaseMount-Set-105-26 mounting bracket</b> Screws &amp; brackets for mounting devices with dimensions 105x26mm in DeviceCarriers</p>	A7000020

## MORE VARIANTS

Description	Article number
<b>RemoteAccess-CPU Basic</b> Computer module to connect a virtual machine to a digital matrix switch via CAT cable	A2320342
<b>RemoteAccess-CPU incl. PowerPack</b> Computer module to connect a virtual machine to a digital matrix switch via CAT cable	A2320343
<b>RemoteAccess-CPU-Fiber(M) Basic</b> Computer module to connect a virtual machine to a digital matrix switch via fiber multimode	A2320350
<b>RemoteAccess-CPU-Fiber(M) Incl. PowerPack</b> Computer module to connect a virtual machine to a digital matrix switch via fiber multimode	A2320351
<b>RemoteAccess-CPU-Fiber(M)-UG Basic</b> Computer module to connect a virtual machine to a digital matrix switch via fiber multimode	A2320362
<b>RemoteAccess-CPU-Fiber(M)-UG Incl. PowerPack</b> Computer module to connect a virtual machine to a digital matrix switch via fiber multimode	A2320363
<b>RemoteAccess-CPU-Fiber(S) Basic</b> Computer module to connect a virtual machine to a digital matrix switch via fiber singlemode	A2320352
<b>RemoteAccess-CPU-Fiber(S) Incl. PowerPack</b> Computer module to connect a virtual machine to a digital matrix switch via fiber singlemode	A2320353
<b>RemoteAccess-CPU-Fiber(S)-UG incl. PowerPack</b> Computer module to connect a virtual machine to a digital matrix switch via fiber singlemode	A2320365
<b>RemoteAccess-CPU-UG Basic</b> Computer module to connect a virtual machine to a digital matrix switch via CAT cable	A2320346
<b>RemoteAccess-CPU-UG Incl. PowerPack</b> Computer module to connect a virtual machine to a digital matrix switch via CAT cable	A2320347

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +49 271 23872-333  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)